Lapp UL Listed Products Conforming to NFPA 79 2007

PRODUCT	APPLICATION	KEY FEATURES
OLFLEX® TRAY II: Shielded & Un	FLEX® TRAY II: Shielded & Unshielded	
Compliant Status: Always	Stationary Control	Tray rated for extended runs, no need for conduit. Highly flexible for ease of installation, save time and money, highly oil and chemical resistant. MTW all sizes
OLFLEX® TC 600 Compliant Status: 14 AWG & Larger- Always	Stationary Control	Contractor grade tray cable with UL TC-ER approval, no need for conduit. MTW sizes 14 AWG and larger
OLFLEX® CONTROL TM FEEX CONTROL TM-(AS) TYPE TO EIR BUY CASH AVAILED (1846) Compliant Status: Always	Stationary Control	Flexible and oil resistant tray and machine cable. MTW all sizes
OLFLEX® CONTROL M MARKE CONSILE SIGNIFIC TO CONTROL CONTROL CONTROL FOR SAME Compliant Status: Always	Stationary Control	Flexible and oil resistant MTW cable for PUR jacketed alternative. MTW all sizes
OLFLEX® FORTIS Compliant Status: Always	Stationary Control	Flexible at -40°C and Oil Res I & II, suitable for tray, machine, and cold temperature applications.
OLFLEX® 190: Shielded & Unshie	Ided Stationary Control	All advantages of 190 cable plus MTW rating
OLFLEX® Auto I OLFLEX AUTO-I (UL) TC-ER OR MTW 90°C 6500 — CSA AWM FT4 pb/fc) Compliant Status: Always	Stationary Control	Available in blue and red conductors to differentiate DC and AC control circuits. MTW sizes 16 & 18 AWG
OLFLEX® CHAIN 879: Shielded &	Unshielded	
Compliant Status: Always	Continuous Flex Control	Designed for continuous flex cable tracks or chains, meets Oil Res I/II for long service life.
OLFLEX® Auto X OLFLEX* AUTOX (UL) TIC-ER OR MITW SUIC 6009 — CSA AWM FF4 (1994-) Compliant Status: Allways	Continuous Flex Control	Designed for continuous flex cable tracks or chains, highly oil and chemical resistant. MTW sizes 18 & 16 AWG
OLFLEX® VFD Slim OUTE WORDSTRICT CONTROL CONT	Stationary VFD Cable	Reduced diameter, flexible VFD cable with "Lapp Surge Guard" with UL and CSA TC approval. MTW all sizes
OLFLEX® VFD REMAIN AND PROPERTY OF A COMPILED STATES OF A 1/107	Stationary VFD Cable	Oil resistant 1000V VFD cable with Bus Drop approval MTW sizes 14 AWG to 2 AWG
OLFLEX® with Signal OUTLEY WO WE BOALA CALL THE SHEET SEA AND	Stationary VFD Cable	Oil resistant VFD Cable with a shielded pair for a brake or for temperature control.
OLFLEX® SDP TC BLADE SEP TO JULY THE TO AN OLE RES NO EPOR AND COLOR—(JULY OC PT & COLOR AND PT)	Motor Supply Power	Stationary severe duty power cable with specially formulated oil and chemical
	and BUS Cable	resistant elastomeric alloy jacket