

# Cable Recommendations for Common Coolants Used in Harsh Environments

Fluid Mfg.	Product	90/150/ 190/890/ 891	VFD/ VFD with Signal	VFD Slim U-190, TRAY II UNI 300	855P	890P 891P 900P	490P 492P 590P	CRF	EWKF	SiHF	HAR	SKINTOP® Clamps
		O-PVC	O-PVC	F-PVC	PUR	PUR	PUR	TPE	Silicone	Silicone	Neo	PA
Argent	H-114-LS	G	E	*	E	+	G	+	+	+	+	+
Argent	H-114-M	E	G	*	G	F	G	E	G	*	E	+
Argent	MS-5710-CG	G	E	G	E	+	+	+	+	+	+	+
Argent	MS5710F	E	E	G	G	G	F	E	E	E	E	+
Armour	Lard	E	G	*	G	E	E	+	E	E	*	E
Blaser Swiss	Vasco 1000/Art.2800	E	E	F	E	+	E	+	+	+	+	+
Blaser Swiss	Grindex Univ./Art.882	E	E	G	E	+	E	+	+	+	+	+
Blaser Swiss	Grindex Univ./Art892	F	F	G	G	*	*	E	E	E	E	+
Buckeye	Safe-T-Fluid #4	E	E	*	E	+	E	+	+	+	+	+
Buckeye	Safe-T-Oil #4	E	E	*	G	E	E	E	G	E	E	+
Buckeye	CT9612	E	G	*	E	+	G	+	+	+	+	+
Castrol	WY1-938A	E	G	G	E	+	+	+	+	+	+	+
Castrol	WY3-010C	E	E	*	E	*	G	+	G	F	E	E
Castrol	Syntillo 1023	G	E	G	E	+	+	+	+	+	+	+
Castrol	WS3-020A	G	G	F	E	+	+	+	+	+	+	+
Castrol	Clearedge 6519	E	E	G	G	+	+	+	+	+	+	+
Castrol	Clearedge 6550	G	E	F	G	+	+	+	+	+	+	+
Castrol	Superedge 6768	E	E	*	F	+	+	+	+	+	+	+
Castrol	GTX-SW30- Oil	E	G	*	G	+	+	+	+	+	+	+
Castrol	Type F Transmission	E	E	E	E	+	+	+	+	+	+	+
Castrol	DEXRON III Mercon	E	E	*	E	+	+	+	+	+	+	+
Castrol	Cooledge 8600	E	G	*	*	*	E	G	G	E	E	+
Castrol	Ilogrind FGO Series	E	G	*	F	G	E	E	E	E	E	+
Chem Tech	CT9612 (2)	E	G	F	E	+	E	+	+	+	+	+
Chem Tech	Tech Cool 3404MG	E	G	*	G	E	E	+	E	E	E	E
Chlorox	Sodium Hypochlorite	E	G	G	F	F	F	+	E	E	*	F
Cin. Millicron	Milpro 6000	E	E	*	E	E	E	E	E	E	E	+
Cin. Millicron	Quantalube 270	E	E	*	E	G	G	E	E	E	E	+
CITGO	Citcool 22 Conc.	E	E	*	F	G	G	+	+	E	E	E
CITGO	Citcool 33 Conc.	E	E	E	F	G	G	+	+	E	E	E
CITGO	Sentry 19	E	E	*	G	E	E	+	+	E	G	E
CITGO	Cutting Oil NC 205	E	E	*	*	F	G	+	+	*	*	E
CITGO	Cutting Oil NC 215	E	E	*	F	F	E	+	+	*	*	E
CLC Lubr.	CLC Finish HX-65	E	G	F	E	E	E	+	E	E	E	E
D.A. Stuart	Excelene 420	E	E	*	G	+	+	+	+	+	+	+
D.A. Stuart	Dascool Nobalt KM	E	G	G	G	E	E	E	E	E	E	+
EPP Tech	400 Klear Kool	G	G	F	G	+	+	+	+	+	+	+
Fuchs Lubr.	GK225	E	G	*	G	F	G	G	G	*	G	+
Fuchs Lubr.	Renogrind FG16	G	G	*	F	G	E	+	+	G	F	E
Fuchs Lubr.	CPD 7003	E	E	*	G	E	E	+	+	F	G	E
Fuchs Lubr.	ECOSYN 975 (4%)	E	E	E	E	E	G	E	E	E	E	+
Fuchs Lubr.	ECOSYN 2205 CO	E	E	E	G	G	E	+	+	G	E	E
Fuchs Lubr.	Melsol Supersol	E	G	*	E	G	G	+	F	F	E	E
Fuchs Lubr.	Tuf Draw 2806-M-100	E	E	E	E	E	E	E	E	E	E	+
G-C Lubr.	Kool Grind 900N	E	G	*	F	G	E	+	+	F	F	E
G-C Lubr.	Kool Grind 960	E	E	*	F	E	E	G	E	F	F	E
G-C Lubr.	Aqua Kool PTC	E	G	*	F	F	G	+	+	G	*	E
G-C Lubr.	Aqua Syn 55	E	F	E	G	G	G	+	+	G	E	E
G-C Lubr.	SintoGrind TT	E	E	*	E	E	E	G	E	E	E	+
Hangsterfers	Missie Lube #1XL	G	G	*	G	E	E	+	+	F	G	E
Hangsterfers	Missie Lube #1XXL	G	G	*	G	F	E	+	+	F	E	+
Hangsterfers	Crystal Cut #322	E	G	E	F	F	F	+	+	G	F	+
Hangsterfers	Crystal Cut #322 @ 5%	E	G	E	E	E	G	+	+	G	G	+
Hangsterfers	R-100	E	E	E	E	E	E	+	E	E	G	E
Hangsterfers	R-100 @ 5%	E	G	E	E	G	E	+	+	E	G	+
Hangsterfers	S500CF	E	E	*	F	G	F	+	G	*	G	E
Hangsterfers	S500CF@10%	E	G	E	G	F	E	+	+	E	G	+
Hangsterfers	Hard Cut 5418	E	E	*	F	G	E	E	E	G	E	+
Hangsterfers	Way Oil #2	G	F	*	G	E	E	+	+	*	E	+

# Cable Recommendations for Common Coolants Used in Harsh Environments

Fluid Mfg.	Product	90/150/ 190/ 890/891	VFD/ VFD with Signal	VFD Slim U-190, TRAY II UNI 300	855P	890P 891P 900P	490P 492P 590P	CRF	EWKF	SiHF	HAR	SKINTOP® Clamps
		O-PVC	O-PVC	F-PVC	PUR	PUR	PUR	TPE	Silicone	Silicone	Neo	PA
Hangsterfers	Antiwear 32	G	E	G	G	E	E	+	+	*	E	+
Hangsterfers	Antiwear 66	G	E	G	G	E	E	+	+	*	E	+
Hanilo	171	E	E	*	F	E	E	E	*	*	E	+
Humoco	Iodine	G	G	E	*	E	G	E	E	G	E	+
Itech	CT9612 (3)	E	G	*	E	+	E	+	+	+	+	+
J & J	Mineral Oil	E	G	*	E	E	E	+	F	E	G	E
Lubrisystems	Lubra-Cut UMC	E	E	E	F	G	E	+	+	E	G	+
Master Chem.	Trim O D250	E	G	F	G	F	E	G	G	E	E	+
Master Chem.	Trim VHP E210	E	E	G	*	G	G	E	E	E	E	+
Master Chem.	Trim WB 9303 12 2	E	E	*	E	*	G	G	F	F	E	+
Mobile	Mobile Met Upsilon	G	G	*	G	+	E	+	+	+	+	+
Mobile	DTE 11M	E	E	*	G	G	E	G	E	E	E	+
Mobile	DTE FM 32	E	E	*	E	G	E	G	E	F	E	+
Monsanto	Glacier Motor	E	E	G	G	G	E	E	E	G	E	+
Motorex	SwissCool 7300 CF	E	G	F	F	E	G	+	E	G	E	E
Mullen	1270-4	E	G	*	E	+	E	+	+	+	+	+
NASCO	Acetone	*	*	*	E	F	*	E	E	E	G	+
National Oil	Nocco Grind (11) Conc.)	G	E	*	F	G	E	+	+	G	F	E
National Oil	Nocco Grind (11) (10%)	E	F	E	G	G	G	+	+	E	E	E
National Oil	Nocco Grind 11	E	E	*	E	E	E	G	E	G	E	+
National Oil	Nocco Grind Modl	E	E	*	E	E	E	G	E	G	E	+
Novamax	Circlene#FG 20AMO	G	E	F	E	+	G	+	+	+	+	+
Novamax	Circlene #FG 67	G	G	*	G	+	G	+	+	+	+	+
Quaker	13413	E	E	*	E	+	E	+	+	+	+	+
Rustick	WS-500A	E	E	*	F	F	G	+	+	F	*	E
Solutia	MCS-2638	E	G	*	G	F	G	E	E	E	E	+
Spartan	Carbide Grinder	G	G	F	E	+	E	+	+	*	+	+
Spartan	Synspar GP	G	G	G	G	+	+	+	+	*	+	+
Spartan	Cutter EXP	E	E	G	F	+	+	+	+	*	+	+
STP	Dot 3 Brake Fluid	G	G	F	*	*	*	E	E	E	E	+
STP	Dot 4 Brake Fluid	G	G	G	*	+	+	+	+	+	+	+
Texaco	Rando Oil HD 26	E	E	*	E	G	E	+	+	*	E	+
Texaco	Cleartex D	E	E	*	G	G	E	+	+	E	F	E
Texaco	Oil Coolant Reno 488	E	G	*	F	F	E	+	+	F	*	E
Uni-Pro	Pro Cool 3000	E	G	F	G	*	G	+	E	G	F	E
WD-40	WD-40	E	E	*	G	G	E	E	E	F	E	+
Wesson	Vegetable Oil	E	G	*	F	E	E	+	E	G	G	E
Westmont	Bio-Cool 55	E	G	G	G	E	G	+	E	G	E	E
Yushiro Chem	Yushiron Oil #2	E	E	*	F	G	E	+	+	*	E	+
Zip Strip	Denatured Alcohol	E	G	*	G	G	E	E	G	E	E	+
Zip Strip	MEK	*	*	*	*	*	*	E	E	E	G	+
Zip Strip	Naphtha	E	E	E	E	E	E	G	E	E	E	+
Zip Strip	Toluene	*	*	*	G	G	G	E	E	E	G	+
Zip Strip	Xylene	F	*	*	G	G	G	G	F	G	G	+
Zip Strip	Turpentine	E	E	*	E	E	E	G	E	E	E	+

E= Excellent (no measurable changes), G= Good (Slight Change), F= Noticeable Change\* = Consult Sales Rep for design assistance,  
+ = Not Tested

Note: Lubricating Oils/Coolants, Water Soluble Oils & Emulsions and Commercial Products tested at 60° for 5 days, Paint Solvents tested at 23°C for 5 days.

\* If the cable series you need is not listed above, call your Sales Representative for assistance.  
(Not all products tested are listed above)