Valid from: 01.12.2021

EPIC[®] ULTRA H-B 24 AG-QB



Description

- Housing H-B ULTRA: For more reliability
- Optimum, low resistance 360° screening
- All-purpose due to high corrosion resistance and high environmental protection
- Space-saving due to compact dimensions
- Faster than any other comparable system
- High mechanical resistance

General Characteristics

Series Version Locking Protection (DIN EN 60529) Protection (NEMA 250, UL50E) Temperature Range ULTRA H-B 24 Panel mount base Double lever IP 65 (latched) 12 (latched) -40°C to +100°C

Materials and Surfaces

Housing Lever / Bolt Sealing

Standard

Safety Standard Product Features after Zinc die-casting, nickel-plated Stainless steel NBR, conductive

IEC 61984 DIN EN 6988, DIN EN ISO 9227, DIN EN 60068-2-52

Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB70250222EN Version: 02	Page 1 of 3
---	---------------------------------------	-------------

DATA SHEET





EPIC[®] ULTRA H-B 24 AG-QB



Technical Drawings









Good chemical resistance



Corrosion resistant



Installation time



Required space



Robust



Connectors with standart housing



PD 0019/05_04.18EN

Waterproof

Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB70250222EN Version: 02	Page 2 of 3		
We reserve all rights according to DIN ISO 16016.				

Valid from: 01.12.2021



Info

EMC protection, Corrosion-resistant

Application range

In EMC-sensitive environments For fixed and flexible applications (e.g. machinery building, wind tribunes) Construction machinery Electric motor manufacturing

Product features

Housing pluggable with standart housing Corrosion resistant according to DIN EN 6988 Resistance to cyclic salt spray is tested according to DIN EN 60068-2-52, severity level 2 Salt spray testing according to DIN EN ISO 9227, method NSS, period of test 480 hours

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: MANA2/PDP	Document: DB70250222EN	Page 3 of 3		
Released: IVSE1/PDP	Version: 02	l age 5 01 5		