


0026300	DATA SHEET	
Valid from: 19.07.2018	ÖLFLEX® CLASSIC FD 810 P	

Application

ÖLFLEX® CLASSIC FD 810 P cables are oil resistant high-flexible control cables with an outer sheath of Polyurethane for flexible use and fixed installation subject to medium mechanical stress. They are also suitable for use in dry, damp or wet areas. If using outdoors, observe the indicated temperature range and use with UV protection.

ÖLFLEX® CLASSIC FD 810 P cables are increased resistant to oils and at room temperature largely resistant to acids and alkalis. The outer sheath withstands high mechanical stresses, in particular abrasion and dragging. It is also cut proof and resists microbes and hydrolysis. They are suitable for linear, automated movements. The maximum tensile load is 15 N/mm² of conductor cross-section during installation and operation. Compulsory guidance is not permitted.

Application range:

in power chains or moving machine parts; particularly in wet areas of machine tools and transfer lines; mechanical engineering; suitable for use in measuring, control and regulating circuits; power circuits for electrical equipment used in automation engineering

Design

Design	based on DIN EN 50525-2-51 resp. VDE 0285-525-2-51 DIN EN 50525-2-21 resp. VDE 0285-525-2-21
Conductor	extra fine wire strands of bare copper acc. to IEC 60228 resp. VDE 0295, Class 6
Core insulation	LAPP special PVC compound P8/1 T12 acc. to EN 50363-3 resp. VDE 0207-363-3 with increased requirements acc. to LAPP specification
Core identification	acc. to VDE 0293-1, with or without GN / YE ground conductor, black cores with white numbers acc. to EN 50334 resp. VDE 0293-334
Outer sheath	Polyurethane compound Tmpu acc. to EN 50363-10-2 resp. VDE 0207-363-10-2 colour: silvergrey, similar RAL 7001

Electrical properties at 20°C

Nominal voltage	U ₀ / U:	300 / 500 V AC
Test voltage	core / core:	4000 V


Mechanical and thermal properties

Min. bending radius	flexible application: up from 7,5 x outer diameter fixed installation: 4 x outer diameter
Bending cycles and power chain operation parameters	See Selection Table A2-1 in the appendix of our online catalogue For use in power chains: Please comply with assembly guideline Appendix T3
Temperature range	flexible application: -5 °C up to +70 ° max. conductor temp. fixed installation: -40 °C up to +80 °C max. conductor temp.
Flammability	acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2
UV-resistance	acc. to EN ISO 4892-2-2006, method A (change of colour allowed)
Ozone resistance	acc. to EN 50396 resp. VDE 0473-396, method B
Oil resistance	acc. to EN 50363-10-2 resp. VDE 0207-363-10-2
MUD resistance	acc. to IEC 67892-4, Annex D

Creator: LABU/PDC Released: HAPF/PDC	Document: DB0026300EN Version: 10	Page 1 of 2
---	--------------------------------------	-------------

We reserve all rights according to DIN ISO 16016.

PD 0019/05_04.18EN

0026300	DATA SHEET	
Valid from: 19.07.2018	ÖLFLEX® CLASSIC FD 810 P	

Tests

acc. to IEC 60811, EN 50395, EN 50396

EU Directives

These cables are conform to the EU-Directives 2014/35/EU (Low Voltage Directive)

Creator: LABU/PDC Released: HAPF/PDC	Document: DB0026300EN Version: 10	Page 2 of 2
---	--------------------------------------	-------------

We reserve all rights according to DIN ISO 16016.

PD 0019/05_04.18EN