


	<b>DATA SHEET</b>	
Valid from: 05-12-2018	<b>FLEXIMARK® Steel cable ties LS and LSC</b>	

For cable and pipe marking.  
 High quality stainless steel cable ties (SS2348, AISI-316L). For demanding aggressive environment.  
 Used together with FLEXIMARK® Stainless steel marking. Mounted with FLEXIMARK® Cable tie plier HT-338.  
 Available with and without polyester coating. Different lengths and widths available in the assortment.  
 Provided with efficient roller ball locking device.



**Technical data**

Material:	Stainless steel according to EN 1.4404 (SS2348, AISI-316L)
Temperature range:	-80°C up to +539°C (coated ties up to +150°C)
Resistance:	Acid-resistance
Approval:	Achilles JQS, UL, DNV-GL, Lloyds, Bureau Veritas
Lengths (widths 4,6 mm):	100, 125, 150, 200, 360, 520, 680, 840,
Lengths (widths 7,9 mm):	200, 360, 520, 680, 840, 1200, 1400, 1016 mm and 100 m
Steel cable ties LS:	without polyester coating
Steel cable ties LSC:	with polyester coating


**Mounting:**

FLEXIMARK® Steel cable ties are easily mounted together with FLEXIMARK® Cable tie plier.


**Advantages:**


Durable marking for aggressive and demanding environments.  
 Easy and fast mounting with FLEXIMARK® Cable tie plier HT-338.  
 High quality stainless steel material (SS2348, AISI-316L).  
 Chemical resistance.  
 Cable ties for indoor and outdoor.  
 Delivered in different lengths.  
 FLEXIMARK® Steel cable ties LSC with polyester coating with softer edges.


Creator: Fleximark/LR	Document: DB61812947EN FLEXIMARK Steel cable ties LS LSC Version: 02	Page 1 of 3
-----------------------	---	-------------

	<b>DATA SHEET</b>	
Valid from: 05-12-2018	<b>FLEXIMARK® Steel cable ties LS and LSC</b>	


**Product data:**

<b>FLEXIMARK® Steel cable ties LS</b>					
					
E-nr.	LAPP Part no.	Article designation	Size (mm)	Content (pcs/unit)	PU
1516600	61812947	LS 4.6x100	4.6x100	100	1
1516602	61812948	LS 4.6x125	4.6x125	100	1
1516604	61812949	LS 4.6x150	4.6x150	100	1
1516606	61812950	LS 4.6x200	4.6x200	100	1
1516608	61812960	LS 4.6x360	4.6x360	100	1
1516610	61812970	LS 4.6x520	4.6x520	100	1
1516641	61812980	LS 4.6x680	4.6x680	100	1
1516642	61812990	LS 4.6x840	4.6x840	100	1
1516611	61813000	LS 7.9x200	7.9x200	100	1
1516612	61813010	LS 7.9x360	7.9x360	100	1
1516613	61813020	LS 7.9x520	7.9x520	100	1
1516614	61813030	LS 7.9x680	7.9x680	100	1
1516643	61813040	LS 7.9x840	7.9x840	100	1
1517273	61813050	LS 7.9x1016	7.9x1016	100	1
1516644	61813083	LS 7.9x1200	7.9x1200	100	1
1516645	61812991	LS 7.9x1400	7.9x1400	100	1

<b>FLEXIMARK® Steel cable ties LSC</b>					
(with polyester coating)					
					
E-nr.	LAPP Part no.	Article designation	Size (mm)	Content (pcs/unit)	PU
1516630	61813085	LSC 4.6x100	4.6x100	100	1
1516632	61813086	LSC 4.6x125	4.6x125	100	1
1516634	61813087	LSC 4.6x150	4.6x150	100	1
1516636	61813088	LSC 4.6x200	4.6x200	100	1
1516638	61813089	LSC 4.6x360	4.6x360	100	1
1516640	61813090	LSC 4.6x520	4.6x520	100	1
1516651	61813091	LSC 4.6x680	4.6x680	100	1
1516652	61813092	LSC 4.6x840	4.6x840	100	1
1516653	61813093	LSC 7.9x200	7.9x200	100	1
1516654	61813094	LSC 7.9x360	7.9x360	100	1
1516655	61813096	LSC 7.9x520	7.9x520	100	1
1516656	61813097	LSC 7.9x680	7.9x680	100	1
1516657	61813098	LSC 7.9x840	7.9x840	100	1

<b>FLEXIMARK® Steel cable ties LS</b>					
(on a roll with accessories)					
					
E-nr.	LAPP Part no.	Article designation	Size (mm/m)	Content (pcs/unit)	PU
1516647	61812946	Head lock 4.6	11,5 mm x6,4 M	100	1
1516648	61812992	Head lock 7.9	13,5 mm x10,6 M	100	1
1516649	61812945	LS 4.6x100M	4.6 mm x100 M	1 (100m)	1
1516650	61813084	LS 7.9x100M	7.9 mm x 100 M	1 (100m)	1

Creator: Fleximark/LR	Document: DB61812947EN FLEXIMARK Steel cable ties LS LSC Version: 02	Page 2 of 3
-----------------------	---	-------------

	<b>DATA SHEET</b>	
Valid from: 05-12-2018	<b>FLEXIMARK® Steel cable ties LS and LSC</b>	

**Related products**

FLEXIMARK® Steel cable ties are used for mounting FLEXIMARK® Stainless steel marking, made with the same stainless steel material (SS2348, AISI-316L).  
 FLEXIMARK® Stainless steel marking is available with holders and character strips for mounting on site, and also customized ready-embossed according to customer specifications.



For easier and more efficient mounting we recommend the FLEXIMARK® Cable tie plier.  
 This tool automatically tightens and cuts stainless steel ties, coated and uncoated.  
 It can handle cable ties in widths up to 7.9 mm and thickness up to 0.3 mm.



**Note:**

Pictures are not to scale and do not represent detailed images of each product.

Creator: Fleximark/LR	Document: DB6 18 12947EN FLEXIMARK Steel cable ties LS LSC Version: 02	Page 3 of 3
-----------------------	---	-------------