



TOSIBOX® 150



Benefits

- SIMPLE - Build and manage secure IoT infrastructure in minutes
- SECURE - Tested & audited security
- MODULAR - Unlimited expandability and flexibility
- COMPATIBLE - Integrate seamlessly with legacy and future systems
- UNIQUE - Globally patented point-to-point connection

Application range

- Remote access and networking device for secure access of HMIs, PLCs, PCs and other devices or systems over the Internet.

Product features

- Patented TOSIBOX® Plug & Go™ connection method takes you out of the box and into use in less than 5 minutes, without the need for software installations, network configurations or special IT skills

- NAT and firewall friendly
- VPN throughput up to 10 MB/s, end-to-end encryption between TOSIBOX® devices
- Up to 10 concurrent VPN connections
- Reliability with TosiOnline™ - automatic re-connection of dropped connections

Product Make-up

- Cast aluminium casing
- 132 mm x 99 mm x 35.5 mm / 5.2" x 3.9" x 1.4" (L x W x H)
- Weight 593 g / 1.31 lbs (net weight article)
- Accessories in package include: RJ-45 Cat6 Ethernet cable, USB extension cable, 2 x WLAN antennas, 2 dBi, AC Adapter: Input 100 240V AC, DC input plug, DIN rail mounting bracket

Technical data

- Operating temperature -20 °C to +50 °C
- Storage temperature -40 °C to +70 °C

Article number	Article description
3806221	TOSIBOX LOCK 150

- If not otherwise specified, all values relating to the product are nominal values. Other value information, such as tolerances, for example, can be obtained on request where available and released for publishing.
- Photographs are not to scale and do not represent detailed images of the respective products.