



TOSIBOX® LOCK 200 without power supply

Industrial router with firewall and secure PLUG & GO™ connectivity



Benefits

- SIMPLE - Build and manage secure IoT infrastructure in minutes
- SECURE - Tested & audited security
- MODULAR - Unlimited expandability and flexibility
- COMPATIBLE - Integrate seamlessly with legacy and future systems
- UNIQUE - Globally patented point-to-point connection

Application range

- Remote access and networking device for secure access of HMIs, PLCs, PCs and other devices or systems over the Internet

Product features

- Patented TOSIBOX® Plug & Go™ connection method takes you out of the box and into use in less than 5 minutes, without the need for software installations, network configurations or special IT skills
- NAT and firewall friendly
- Improved VPN throughput up to 15 MB/s
- New streamlined web user interface
- Up to 50 concurrent VPN connections

Product Make-up

- Cast aluminium casing
- 140 mm x 36 mm x 125 mm / 5.51" x 1.42" x 4.92" (L x W x H)
- Weight 530 g / 1.17 lbs
- Accessories in package include: USB extension cable, Ethernet cable, AC adapter: Input 100-240 V AC, 50/60 Hz, Output 24.0 V DC, 0.8 A, DIN rail mounting bracket, Cable saddle and DC input plug

Technical data



IP20



Operating temperature -20°C to +50°C
Storage temperature -40°C to +70°C

Article number	Article description
3806222	TOSIBOX LOCK 200 WITHOUT PS

- If not otherwise specified, all values relating to the product are nominal values. Other value information, such as tolerances, for example, can be obtained on request where available and released for publishing.
- Photographs are not to scale and do not represent detailed images of the respective products.