



ÖLFLEX® UNIPLUS HFFR

Halogen free flame retardant single core



Info

- Halogen free

Benefits

- Time-saving assembly
- Highly flexible due to special insulation compound as per LAPP specifications
- Protection of human life and the environment, Thanks to the avoidance of the formation of acid and smoke in case of fire

Application range

- For wiring of lamps, devices, switch gear cabinets and distribution boxes

- For installation in tubes, as well as in closed installation ducts or protected installations
- For use in dry rooms
- In application area with a high density of people or valuable assets

Product features

- Flame retardant (FR)- IS 108 10-53/IEC 60332.1

Product Make-up

- Stranded Annealed Bare copper
- Low Smoke Zero Halogen compound

Technical data

- Core identification code**
Coloured
- Conductor stranding**
Fine wire stranded Class 5 in acc. to IS 8130-1984/IEC 60228
- Minimum bending radius**
6 X OD
- Nominal voltage**
Up to and including 1 100 V
- Temperature range**
Up to +70°C for fixed installations

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Colour	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® UNIPLUS HFFR					
4725001U	1 X 0.5	2.6	green-yellow	4.6	9
4725002U	1 X 0.75	2.8	green-yellow	7.2	12
4725003U	1 X 1.0	3.0	Yellow	9.6	15
4726011U	1 X 1.5	3.4	black	14.4	21
4726031U	1 X 1.5	3.4	brown	14.4	21
4726021U	1 X 1.5	3.4	blue	14.4	21
4726141U	1 X 1.5	3.4	dark blue	14.4	21
4726121U	1 X 1.5	3.4	green	14.4	21
4726001U	1 X 1.5	3.4	green-yellow	14.4	21
4726061U	1 X 1.5	3.4	grey	14.4	21
4726091U	1 X 1.5	3.4	orange	14.4	21
4726081U	1 X 1.5	3.4	pink	14.4	21
4726041U	1 X 1.5	3.4	red	14.4	21
4726161U	1 X 1.5	3.4	ultra marine blue	14.4	21
4726071U	1 X 1.5	3.4	violet	14.4	21
4726051U	1 X 1.5	3.4	white	14.4	21
4726111U	1 X 1.5	3.4	yellow	14.4	21
4726012U	1 X 2.5	4.1	black	24.0	33
4726032U	1 X 2.5	4.1	brown	24.0	33
4725002U	1 X 2.5	4.1	blue	24.0	33
4726122U	1 X 2.5	4.1	green	24.0	33
4726002U	1 X 2.5	4.1	green-yellow	24.0	33
4726062U	1 X 2.5	4.1	grey	24.0	33
4726042U	1 X 2.5	4.1	red	24.0	33
4726052U	1 X 2.5	4.1	white	24.0	33
4726112U	1 X 2.5	4.1	green-yellow	24.0	33
4726003U	1 X 4	4.8	green-yellow	38.4	50
4726004U	1 X 6	5.3	green-yellow	57.6	74
4726005U	1 X 10	7.0	green-yellow	96.0	122
4726006U	1 X 16	8.1	green-yellow	153.6	185
4726007U	1 X 25	10.2	green-yellow	240.0	288
4726008U	1 X 35	11.7	green-yellow	336.0	391
4726009U	1 X 50	13.9	green-yellow	480.0	557
4727001U	1 X 70	16.0	green-yellow	672.0	770
4727002U	1 X 95	18.2	green-yellow	912.0	1033
4727003U	1 X 120	20.2	green-yellow	1152.0	1283
4727004U	1 X 150	22.5	green-yellow	1440.0	1611
4727005U	1 X 185	24.9	green-yellow	1776.0	1988
4727006U	1 X 240	28.4	green-yellow	2304.0	2561
4722001U	1 X 300	31.0	green-yellow	2615.0	2915

- If not otherwise specified, all values relating to the product are nominal values. Other value information, such as tolerances, for example, can be obtained on request where available and released for publishing.
- Photographs are not to scale and do not represent detailed images of the respective products.