


SKINTOP® STR-M Gland & Nut Combi Pack

SKINTOP® STR-M, increased oil-resistant plastic cable gland with permanent vibration protection and reducing seal insert



Info

- Now with IP69 approval! Proven to withstand the most demanding cleaning procedures for industrial machinery with high-pressure cleaners and hot water!

Benefits

- High oil-resistance for maximum reliability
- Permanent vibration protection
- Wide, variable clamping ranges
- Optimum strain relief
- Various accessories (e.g. multiple sealing inserts)

Application range

- With reducing seal insert, to seal cables with smaller outer diameters

Norm references / Approvals

- UL File Nr. E79903
- GGVS: TÜ.EGG.020-95

Product Make-up

- Metric connection thread acc. to DIN EN 60423
- Basis for technical information DIN IEC 62444

Technical data



Classification ETIM 5

ETIM 5.0 Class-ID: EC000441
ETIM 5.0 Class-Description: Cable screw gland



Classification ETIM 6

ETIM 6.0 Class-ID: EC000441
ETIM 6.0 Class-Description: Cable screw gland



Colour delivered

Silver grey (RAL 7001)
Light grey (RAL 7035)
Black (RAL 9005)



Material

Body: Polyamide
Seal: CR



Temperature range

Fixed: -40°C to +100°C
Dynamic: -20°C to +100°C



Protection rating

IP 66
IP 68 - 5 bar
IP 69
NEMA Type 1, 12



Caution

Refer to Appendix T21 for the installation dimensions and torques
Size M 40 x 1,5 up to M 63 x 1,5 with O-ring

Article number	Description	Colour	Clamping range ØF (mm)	SW wrench size (mm)	Overall length, C (mm)	Thread length, D (mm)	Pieces/PACK
SKINTOP® STR-M COMBI PACK							
3806024	SKINTOP STR-M 12 X 1,5 + LOCKNUT SGY	silver grey	2 - 5	15	30.0	8	10
3806025	SKINTOP STR-M 16 X 1,5 + LOCKNUT SGY	silver grey	3.5 - 7	19	34.0	8	10
3806026	SKINTOP STR-M 20 X 1,5 + LOCKNUT SGY	silver grey	4 - 10	25	37.0	9	10
3806027	SKINTOP STR-M 25 X 1,5 + LOCKNUT SGY	silver grey	5 - 13	30	40.0	10	10
3806028	SKINTOP STR-M 32 X 1,5 + LOCKNUT SGY	silver grey	6 - 15	36	47.0	10	5
3806029	SKINTOP STR-M 40 X 1,5 + LOCKNUT SGY	silver grey	9 - 23	46	52.0	10	5
3806030	SKINTOP STR-M 50 X 1,5 + LOCKNUT SGY	silver grey	24 - 29	55	62.0	12	1
3806031	SKINTOP STR-M 63 X 1,5 + LOCKNUT SGY	silver grey	28 - 39	66	71.0	12	1
3806032	SKINTOP STR-M 12 X 1,5 + LOCKNUT BK	black	2 - 5	15	30.0	8	10
3806033	SKINTOP STR-M 16 X 1,5 + LOCKNUT BK	black	3.5 - 7	19	34.0	8	10
3806034	SKINTOP STR-M 20 X 1,5 + LOCKNUT BK	black	4 - 10	25	37.0	9	10
3806035	SKINTOP STR-M 25 X 1,5 + LOCKNUT BK	black	5 - 13	30	40.0	10	10
3806036	SKINTOP STR-M 32 X 1,5 + LOCKNUT BK	black	6 - 15	36	47.0	10	5
3806037	SKINTOP STR-M 40 X 1,5 + LOCKNUT BK	black	9 - 23	46	52.0	10	5
3806038	SKINTOP STR-M 50 X 1,5 + LOCKNUT BK	black	24 - 29	55	62.0	12	1
3806039	SKINTOP STR-M 63 X 1,5 + LOCKNUT BK	black	28 - 39	66	71.0	12	1
3806040	SKINTOP STR-M 12 X 1,5 + LOCKNUT LGY	light grey	2 - 5	15	30.0	8	10
3806041	SKINTOP STR-M 16 X 1,5 + LOCKNUT LGY	light grey	3.5 - 7	19	34.0	8	10
3806042	SKINTOP STR-M 20 X 1,5 + LOCKNUT LGY	light grey	4 - 10	25	37.0	9	10
3806043	SKINTOP STR-M 25 X 1,5 + LOCKNUT LGY	light grey	5 - 13	30	40.0	10	10
3806044	SKINTOP STR-M 32 X 1,5 + LOCKNUT LGY	light grey	6 - 15	36	47.0	10	5
3806045	SKINTOP STR-M 40 X 1,5 + LOCKNUT LGY	light grey	9 - 23	46	52.0	10	5
3806046	SKINTOP STR-M 50 X 1,5 + LOCKNUT LGY	light grey	24 - 29	55	62.0	12	1
3806047	SKINTOP STR-M 63 X 1,5 + LOCKNUT LGY	light grey	28 - 39	66	71.0	12	1

- If not otherwise specified, all values relating to the product are nominal values. Other value information, such as tolerances, for example, can be obtained on request where available and released for publishing.
- Photographs are not to scale and do not represent detailed images of the respective products.