

	Anschluss- technik	Leiter	Winkel	Merkmal, Besonder- heit	PG SS	Artnr.	Bezeichnung	
Profibus D-Sub Steckverbinder, Gehäuse Kunststoff metallisiert								
	Fast Connect	massiv 0,64 mm ²	35°			21700511	ED-PB-35-FC	
					PG	21700513	ED-PB-35-PG-FC	
			90°			21700502	ED-PB-90-FC	
					PG	21700501	ED-PB-90-PG-FC	
				LED		21700547	ED-PB-90-LED-FC	
					PG	21700546	ED-PB-90-PG-LED-FC	
		180°				21700544	ED-PB-AX-FC	
		flexibel 0,64 mm ²		35°			21700514	ED-PB-35-FC-FLEX
			PG			21700515	ED-PB-35-PG-FC-FLEX	
			90°			21700528	ED-PB-90-FC-FLEX	
					PG	21700527	ED-PB-90-PG-FC-FLEX	
				LED		21700549	ED-PB-90-LED-FC-FLEX	
					PG	21700539	ED-PB-90-PG-LED-FC-FLEX	
				180°			21700545	ED-PB-AX-FC-FLEX
	Schraub- Anschluss			massiv + flexibel ≤ 1 mm ²	35°			21700507
		PG	21700506				ED-PB-35-PG	
		90°				21700504	ED-PB-90	
					PG	21700503	ED-PB-90-PG	
			LED			21700530	ED-PB-90-LED	
					PG	21700529	ED-PB-90-PG-LED	
			ATEX			21700543	ED-PB-90-ATEX	
					PG	21700542	ED-PB-90-PG-ATEX	
			Repeater			21700541	ED-PB-90-RP-PG	
			180°				21700505	ED-PB-AX
		Federzug	massiv ≤ 0,5 mm ²		90°		21700509	ED-PB-90-ST
						PG	21700508	ED-PB-90-PG-ST
		M12	massiv + flexibel		90°		21700521	ED-PB-90-M12
						PG	21700520	ED-PB-90-PG-M12
CAN Bus / DeviceNet D-Sub Steckverbinder, Gehäuse Kunststoff metallisiert								
	Schraub- Anschluss	massiv + flexibel ≤ 1 mm ²	90°			21700537	ED-PB-90	
					PG	21700536	ED-PB-90-PG	
		180°			21700538	ED-PB-AX		