

Product Range Update: ÖLFLEX SERVO 730 → ÖLFLEX CLASSIC 110 BK 0,6/1kV

Product comparison:

	ÖLFLEX SERVO 730	ÖLFLEX CLASSIC 110 BK 0,6/1kV
Outer sheath	grey	black
Features/ Application		UV-resistant and wheather-proof, direct burial
Catalogue program	4 G 1,5 up to 4 G 16	4 G 0,75 up to 4 G 120

	ÖLFLEX SERVO 730 CY	ÖLFLEX CLASSIC 110 CY BK 0,6/1kV
Inner sheath	Grey	Black
Outer sheath	Grey	Black
Features/ Application		UV-resistant and wheather-proof, direct burial
Catalogue program	4 G 1,5 up to 4 G 25	4 G 0,75 up to 4 G 120

Cross Reference:

	ÖLFLEX SERVO 730			ÖLFLEX CLASSIC 110 BK 0,6/1kV	
Number of cores x mm ²	Part number	Outer diam. /mm		Part number	Outer diam. /mm
4 G 1,5	0036130	10,1	→	1120309	10,8
4 G 2,5	0036131	11,9	→	1120342	12,2
4 G 4	0036132	13,7	→	1120360	13,8
4 G 6	0036133	15,0	→	1120366	15,1
4 G 10	0036134	18,8	→	1120370	18,7
4 G 16	0036135	21,9	→	1120374	21,3

	ÖLFLEX SERVO 730 CY			ÖLFLEX CLASSIC 110 CY BK 0,6/1kV	
Number of cores x mm ²	Part number	Outer diam. /mm		Part number	Outer diam. /mm
4 G 1,5	0036105	12,1	→	1121309	13,0
4 G 2,5	0036106	14,3	→	1121342	14,6
4 G 4	0036107	15,9	→	1121360	16,2
4 G 6	0036108	17,4	→	1121367	17,7
4 G 10	0036109	21,9	→	1121372	21,7
4 G 16	0036110	24,7	→	1121377	24,3
4 G 25	0036111	30,2	→	1121381	29,8

Colouring:

Product advantages

Relevant differences