



FTG16XHOHM16 600/1000V

CU/MGT/HEPR/IS/OS/LSZH

CPR Class: Cca – s1b, d1, a1

Design

- **Conductor**
Stranded annealed or tinned Copper + Mica glass tape
- **Insulation**
Cross-linked copolymer
- **Individual Screen**
Aluminum/PET + tinned Copper drain wire
- **Overall Screen**
Aluminum/PET + tinned Copper drain wire
- **Outer sheath**
LSZH (low smoke zero halogen)
- **Colour**
Upon request

Special Features

- UV-resistant
- Hydrocarbon and Chemical resistant
- Oil resistant

Type of Application

- Middle-high level CPR classification
- Suitable for installation in constructions and civil engineering buildings with high concentration of people.

Norm references and Approvals

- **Constructive standard**
EN 50288-7
- **CPR**
EU 305/11
EN 50575
- **Hydrocarbon & Oil**
CEI 20-34/0
IEC 60811-404
- **Determination of acidity**
IEC 60754-2
- **Low Smoke Emission**
IEC 61034-2
- **Fire behavior**
IEC 60332-1-2
EN 50399
EN 50200/IEC 60331-1

DoP Number

- CCE_DOP_220001

Technical data

Core identification code:
Pairs: black & white numbered
Triads: black, white, red numbered
Other colors code available on request

Insulation resistance:
1000 MOhm x km

Conductor stranding:
Class 5 IEC 60228

Nominal Voltage U₀/U:
600/1000 V

Test voltage:
C/C 3500 Vac x 5 minute

Temperature range:
during operation: -30° to +70°C
during installation: -5° to +50°C

Minimum Bending Radius:
8 x Outer Diameter

Cross section (mm ²)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
2x2x1	12,3	45,7	250,5
6x2x1	17,7	127,5	487,3
10x2x1	23,2	209,3	830,5
12x2x1	24,2	250,2	885,6
16x2x1	27,1	332,0	1107,8
20x2x1	30,5	413,8	1427,4
24x2x1	34,0	495,6	1785,5
2x2x1,5	13,2	64,9	289,0
6x2x1,5	19,3	185,1	583,9
10x2x1,5	25,2	305,3	1004,2
12x2x1,5	26,1	365,4	1073,5
16x2x1,5	29,3	485,6	1330,1
20x2x1,5	33,1	605,8	1710,2
24x2x1,5	37,0	726,0	2136,9
2x2x2,5	15,2	103,3	381,1
6x2x2,5	22,2	300,3	791,5
10x2x2,5	29,0	497,3	1359,0
12x2x2,5	30,2	595,8	1447,7
16x2x2,5	33,9	792,8	1822,8
20x2x2,5	38,3	989,8	2304,3
24x2x2,5	42,7	1186,8	2883,6

Cross section (mm ²)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
2x3x1	13,9	64,9	337,1
6x3x1	20,0	185,1	701,8
10x3x1	26,2	305,3	1217,4
12x3x1	27,3	365,4	1301,9
16x3x1	30,6	485,6	1650,6
20x3x1	34,4	605,8	2084,8
24x3x1	38,6	726,0	2622,0
2x3x1,5	15,0	93,7	401,7
6x3x1,5	21,8	271,5	845,3
10x3x1,5	28,5	449,3	1464,5
12x3x1,5	29,7	538,2	1568,2
16x3x1,5	33,2	716,0	1990,1
20x3x1,5	37,4	893,8	2513,7
24x3x1,5	42,0	1071,6	3135,2
2x3x2,5	17,2	151,3	533,2
6x3x2,5	25,1	444,3	1142,7
10x3x2,5	32,9	737,3	1975,0
12x3x2,5	34,1	883,8	2151,4
16x3x2,5	38,4	1176,8	2704,5
20x3x2,5	43,7	1469,8	3422,7
24x3x2,5	48,2	1762,8	4342,1

Unless specified, the shown product values are nominal. Detailed values (e.g. tolerances) are available upon request.

Photographs are not to scale and do not represent detailed images of the respective products, technical sheets including detailed constructions and performances are available upon request