



ÖLFLEX® INSTRUM SWA LEAD 180

Armoured, Lead jacketed, Overall screened instrumentation cable
CU/XLPE/OS/PVC/LC/PVC/SWA/PVC



Info

**RE4XOHRLRFR 300 V
EN 50288-7**

Benefits

- Sunlight resistant
- Hydrocarbon and Chemical resistant
- Fire behaviour
- Oil resistant

Product features

Armoured, lead jacketed, twisted pair or triad signal cable, overall screened, XLPE insulated and PVC jacketed

Norm references / Approvals

- **Hydrocarbon & Oil resistance**
CEI 20-34/0
- **Halogen acid gas**
IEC 60754-1 (max 20%)
- **Fire behaviour**
IEC 60332-1-2
IEC 60332-3-22 (Cat. A)

Design

- **Conductor:** Stranded Annealed Copper
- **Core insulation:** XLPE
- **Screen:** OS Aluminum/PET + TC Drain wire
- **Inner sheath:** PVC, black
- **Chemical Barrier:** Lead sheath
- **Inner sheath:** PVC, black
- **Armour:** Galvanized Steel Wire
- **Outer sheath:** PVC, black

Technical data

- Core identification code:**
Pairs are black & white with printed numbers
Triads are black, white, red with printed numbers
- Insulation resistance:**
5000 MOhm x km
- Conductor stranding:**
Class 2 IEC 60228
- Nominal Voltage Uo/U:**
300/300 V
- Test voltage:**
C/C 1500 V x 1 minute
- Temperature range:**
during operation: -30° to +90°C
during installation: -5° to +50°C
- Minimum Bending Radius:**
15 x Outer Diameter

Number cores and mm ² per conductor	Approx. Outer Diameter (mm)	Copper index (kg/km)	Approx. Weight (kg/km)
ÖLFLEX® INSTRUM SWA LEAD 180			
1x2x0,5	13,7	15,1	468
2x2x0,5	16,5	25,4	673
6x2x0,5	19,7	66,7	962
10x2x0,5	23,1	108,0	1.283
12x2x0,5	23,5	128,7	1.332
16x2x0,5	25,4	170,0	1.523
20x2x0,5	28,5	211,3	1.966
24x2x0,5	30,6	252,6	2.244
30x2x0,5	32,1	314,6	2.449
1x3x0,5	14,2	20,2	520
3x3x0,5	18,2	51,2	837
6x3x0,5	21,3	97,7	1.104
10x3x0,5	25,0	159,7	1.486
12x3x0,5	25,5	190,6	1.551
1x2x0,75	14,7	20,2	553
2x2x0,75	17,5	35,7	745
6x2x0,75	21,5	97,5	1.119
10x2x0,75	25,4	159,4	1.506
12x2x0,75	26,8	190,3	1.779
16x2x0,75	29,0	252,2	2.034
20x2x0,75	31,4	314,0	2.397
24x2x0,75	33,8	375,9	2.660
30x2x0,75	36,2	468,7	3.057
1x3x0,75	15,0	27,9	581
3x3x0,75	19,4	74,3	938
6x3x0,75	23,1	143,9	1.325
10x3x0,75	28,5	236,7	1.984
12x3x0,75	29,1	283,1	2.074

Number cores and mm ² per conductor	Approx. Outer Diameter (mm)	Copper index (kg/km)	Approx. Weight (kg/km)
ÖLFLEX® INSTRUM SWA LEAD 180			
1x2x1	15,2	25,6	588
2x2x1	18,6	46,5	868
6x2x1	22,9	130,1	1.292
10x2x1	28,2	213,6	1.930
12x2x1	28,8	255,4	2.013
16x2x1	31,0	338,9	2.357
20x2x1	33,7	422,5	2.704
24x2x1	37,1	506,0	3.184
30x2x1	39,8	631,4	3.804
1x3x1	15,5	36,1	621
3x3x1	20,5	98,7	1.035
6x3x1	24,8	192,7	1.503
10x3x1	30,2	318,0	2.213
12x3x1	31,3	380,7	2.435
1x2x1,5	16,0	36,5	651
2x2x1,5	20,0	68,2	987
6x2x1,5	25,3	195,1	1.546
10x2x1,5	31,4	322,1	2.388
12x2x1,5	32,3	385,5	2.515
16x2x1,5	35,5	512,5	3.029
20x2x1,5	39,5	639,4	3.809
24x2x1,5	42,8	766,3	4.276
30x2x1,5	45,2	956,7	4.836
1x3x1,5	16,7	52,3	702
3x3x1,5	22,6	147,5	1.278
6x3x1,5	28,5	290,3	2.041
10x3x1,5	34,0	480,7	2.785
12x3x1,5	35,6	575,9	3.104

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request. Photographs are not to scale and do not represent detailed images of the respective products

AVAILABLE ALSO IN: Conductor Class 5, Tinned copper conductor, other colors, Armour DSTA