



Conductor resistances and conductor stranding (metric)

Conductor resistances: up to 0.38 mm² as per DIN VDE 0812 and DIN VDE 0881 for stranded conductors, from 0.5 mm² as per IEC 60228/DIN EN 60228 (VDE 0295) for conductors made of soft-annealed copper and single and multi-core cables.

Nominal cross-section in mm ²	Conductor resistances at 20 °C for 1 km in Ω (max. value)			
	made of wires with metal sheath		made of bare wires	
	Class 2	Class 5 + 6	Class 2	Class 5 + 6
0.08		252.0		243.0
0.14		148.0		138.0
0.25		79.9		79.0
0.34		57.5		57.0
0.38		52.8		48.5
0.5	36.7	40.1	36.0	39.0
0.75	24.8	26.7	24.5	26.0
1	18.2	20.0	18.1	19.5
1.5	12.2	13.7	12.1	13.3
2.5	7.56	8.21	7.41	7.98
4	4.70	5.09	4.61	4.95
6	3.11	3.39	3.08	3.30
10	1.84	1.95	1.83	1.91
16	1.16	1.24	1.15	1.21
25	0.734	0.795	0.727	0.780
35	0.529	0.565	0.524	0.554
50	0.391	0.393	0.387	0.386
70	0.270	0.277	0.268	0.272
95	0.195	0.210	0.193	0.206
120	0.154	0.164	0.153	0.161
150	0.126	0.132	0.124	0.129
185	0.100	0.108	0.0991	0.106
240	0.0762	0.0817	0.0754	0.0801
300	0.0607	0.0654	0.0601	0.0641
400	0.0475		0.0470	
500	0.0369		0.0366	
630	0.0286		0.0283	
800	0.0224		0.0221	
1000	0.0177		0.0176	

Example conductor stranding (metric)

Cross-section in mm ²	Multi-wire conductor	Several-wire conductor	Fine-wire conductor	Extra-fine wire conductor			
0.14				~ 18 x 0.10	~ 18 x 0.1	~ 36 x 0.07	~ 72 x 0.05
0.25			~ 14 x 0.15	~ 32 x 0.10	~ 32 x 0.1	~ 65 x 0.07	~ 128 x 0.05
0.34		7 x 0.25	~ 19 x 0.15	~ 42 x 0.10	~ 42 x 0.1	~ 88 x 0.07	~ 174 x 0.05
0.38		7 x 0.27	~ 19 x 0.16	~ 19 x 0.16	~ 48 x 0.1	~ 100 x 0.07	~ 194 x 0.05
0.5	7 x 0.30	7 x 0.30	~ 16 x 0.20	~ 28 x 0.15	~ 64 x 0.1	~ 131 x 0.07	~ 256 x 0.05
0.75	7 x 0.37	7 x 0.37	~ 24 x 0.20	~ 42 x 0.15	~ 96 x 0.1	~ 195 x 0.07	~ 384 x 0.05
1.0	7 x 0.43	7 x 0.43	~ 32 x 0.20	~ 56 x 0.15	~ 128 x 0.1	~ 260 x 0.07	~ 512 x 0.05
1.5	7 x 0.52	7 x 0.52	~ 30 x 0.25	~ 84 x 0.15	~ 192 x 0.1	~ 392 x 0.07	~ 768 x 0.05
2.5	7 x 0.67	~ 19 x 0.41	~ 50 x 0.25	~ 140 x 0.15	~ 320 x 0.1	~ 651 x 0.07	~ 1280 x 0.05
4	7 x 0.85	~ 19 x 0.52	~ 56 x 0.30	~ 224 x 0.15	~ 512 x 0.1	~ 1040 x 0.07	
6	7 x 1.05	~ 19 x 0.64	~ 84 x 0.30	~ 192 x 0.20	~ 768 x 0.1	~ 1560 x 0.07	
10	7 x 1.35	~ 49 x 0.51	~ 80 x 0.40	~ 320 x 0.20	~ 1280 x 0.1	~ 2600 x 0.07	
16	7 x 1.70	~ 49 x 0.65	~ 128 x 0.40	~ 512 x 0.20	~ 2048 x 0.1		
25	7 x 2.13	~ 84 x 0.62	~ 200 x 0.40	~ 800 x 0.20	~ 3200 x 0.1		
35	7 x 2.52	~ 133 x 0.58	~ 280 x 0.40	~ 1120 x 0.20			
50	~ 19 x 1.83	~ 133 x 0.69	~ 400 x 0.40	~ 705 x 0.30			
70	~ 19 x 2.17	~ 189 x 0.69	~ 356 x 0.50	~ 990 x 0.30			
95	~ 19 x 2.52	~ 259 x 0.69	~ 485 x 0.50	~ 1340 x 0.30			
120	~ 37 x 2.03	~ 336 x 0.67	~ 614 x 0.50	~ 1690 x 0.30			
150	~ 37 x 2.27	~ 392 x 0.69	~ 765 x 0.50	~ 2123 x 0.30			
185	~ 37 x 2.52	~ 494 x 0.69	~ 944 x 0.50	~ 1470 x 0.40			
240	~ 37 x 2.87	~ 627 x 0.70	~ 1225 x 0.50	~ 1905 x 0.40			
300	~ 61 x 2.50	~ 790 x 0.70	~ 1530 x 0.50	~ 2385 x 0.40			
400	~ 61 x 2.89		~ 2035 x 0.50				
500	~ 61 x 3.23		~ 1768 x 0.60				
630	~ 91 x 2.97		~ 2286 x 0.60				

NOTE ON STANDARDS:

- For single-wire conductors... (class 1), please see DIN EN 60228 (VDE 0295), table 1
- For multi-wire conductors... (class 2), please see DIN EN 60228 (VDE 0295), table 2
- For fine-wire conductors... (class 5), please see DIN EN 60228 (VDE 0295), table 3
- For extra-fine wire conductors... (class 6), please see DIN EN 60228 (VDE 0295), table 4



single-wire



multi-/several-wire



fine-wire



extra-fine wire