



Rep	Details of components	Dia.mm	Characteristics
1	Filler		<p align="center"><b><u>Electrical features</u></b></p> <p align="center">Operating voltage of the conductors : 30 Volts Test voltage between 2 conductors : 250 Volts / 1 min Lineic resistance : 150 ohms/km</p> <p align="center"><b><u>General features</u></b></p> <p align="center">Operating temperature : -30 to +80 °C</p> <p align="center">Static bending radius ≥ 25 mm Dynamic bending radius ≥ 60 mm Lineic weight : 55 g/m Outer diameter : 6.3 ± 0.3 mm</p> <p align="center">Colour coding : according to DIN 47100</p> <p align="center">Practicable test voltage between 2 conductors : 2000 VAC - 1 mn</p>
2	6 Conductors 0.14 mm <sup>2</sup> Wires in alloy of special high mechanical resistance copper MULTEC insulated (High temperature insulation 200°C)	0.9	
3	Assembling tape		
4	Spinning in alloy of special high mechanical resistance copper	3.8	
5	Protective tape	4.1	
6	Polyurethane sheath (Voltage resistance of the sheath 600V)	6.3	

This document belongs to LAPP MULLER S.A.S. and can not be used without his authorization.

E						
D	12/03/13	AJOUT INFORMATION	Bidou		Besio	
C	11/05/09	AJUSTEMENT EPAISSEUR UL	Montalto		Bruyère	
B	11/05/07	EVOLUTION EN UL	Montalto		Bidou	
A	07/10/05	CREATION FICHE TECHNIQUE	Montalto		Bidou	
Révision	Date	Motif de révision	Etablie par Technicien	VISA	Vérifiée par Resp. B.E.	VISA