

ÖLFLEX® POWER LV 2X LSZH ARM
DS 382002644

valid from: 2018-03-31

Application

ÖLFLEX® POWER LV 2X LSZH ARM is suitable for main power distribution and lighting circuits in residential and commercial buildings. Suitable for direct burial application. UV resistant outer sheath for outdoor application and anti-rodent properties is provided if resistance is required against rodents.

Design

Conductor	annealed bare copper Class II - in accordance to IS 8130
Standard	IS 7098 (Part-I)
Insulation	cross linked polyethylene in accordance to IS 7098-I
Inner Sheath	Zero halogen compound with flame retardant low smoke properties
Outer Sheath	Zero halogen compound with flame retardant low smoke properties
Armouring	aluminium wire armour (WA) GI wire armour (SWA) GI strip armour (SSA)

Electrical properties

Nominal voltage	1100 V
Test voltage	3 KV for 5 minutes

Mechanical properties

Min. bending radius	fixed installation:	18 x cable OD
Temperature range	fixed installation:	-5 °C up to +90 °C max. conductor temperature

Flame and other tests

Flammability	in acc. with IS 10810-53 / IEC 60332-1
Test	acc. to IS 10810
Oxygen Index:	> 30% in accordance to IS 10810(Part-58) / ASTM-D 2863
Temperature index	minimum 250 °C in accordance to IS 10810(Part-64) / ASTM-D 2863
Smoke density	maximum smoke density of 40% in acc. to IS 13360(Part 6/Sec 9) / ASTM-D 2843
Acid gas generation	HCL content maximum 0.5% in acc. to IS 10810(Part-59) / IEC 754-1

ÖLFLEX® POWER LV 2X LSZH ARM
DS 382002644

valid from: 2018-03-31

Article number	Number of cores and mm ² per conductor	Nominal outer diameter (mm)	Copper weight (kg/km) Approx.	Weight (kg/km) Approx.
ÖLFLEX® POWER LV 2X LSZH ARM - R12XHXSVAHX1BK				
382002644	2x1.5	13.7	26.6	1,475.8
382002645	3x1.5	14.2	40.0	1,575.2
382002646	4x1.5	15.0	53.3	1,704.4
382002647	5x1.5	15.8	66.6	1,847.6
382002648	6x1.5	16.7	79.9	1,684.2
382002649	7x1.5	16.7	93.2	1,702.6
382002650	8x1.5	18.1	106.6	1,894.9
382002651	9x1.5	19.1	119.9	2,048.1
382002652	10x1.5	20.1	133.2	1,460.6
382002653	11x1.5	20.1	146.5	1,478.9
382002704	2x2.5	14.5	43.5	1,621.6
382002705	3x2.5	15.1	65.2	1,741.9
382002706	4x2.5	15.9	87.0	1,879.0
382002707	5x2.5	16.9	108.7	1,782.7
382002708	6x2.5	17.9	130.5	1,894.5
382002709	7x2.5	17.9	152.2	1,922.1
382002710	8x2.5	19.9	174.0	2,176.2
382002783	2x4	15.5	69.2	1,815.8
382002784	2x6	16.7	103.6	1,750.5
382002785	2x10	18.5	174.3	2,074.5
382002798	3x4	16.1	103.8	1,934.6
382002799	3x6	17.4	155.4	1,894.7
382002800	3x10	19.8	261.5	2,293.9
382002824	4x4	17.2	138.4	1,843.7
382002825	4x6	18.6	207.2	2,103.2
ÖLFLEX® POWER LV 2X LSZH ARM - R12XHXSVAHX1BK				
382002654	12x1.5	19.0	159.8	2,022.3
382002655	13x1.5	20.2	173.2	1,463.4
382002656	14x1.5	20.2	186.5	1,481.7
382002657	15x1.5	21.0	199.8	1,544.7
382002658	16x1.5	21.0	213.1	1,563.1
382002659	17x1.5	21.9	226.4	1,657.2
382002660	18x1.5	21.9	239.7	1,675.6
382002661	19x1.5	21.9	253.1	1,693.9
382002662	20x1.5	22.9	266.4	1,793.6
382002663	21x1.5	22.9	279.7	1,812.0
382002664	22x1.5	23.9	293.0	1,886.1
382002665	23x1.5	23.9	306.3	1,904.5
382002666	24x1.5	24.9	319.7	2,004.2
382002667	25x1.5	24.9	333.0	2,022.5
382002668	26x1.5	24.9	346.3	2,040.9
382002669	27x1.5	25.4	359.6	2,112.7
382002670	28x1.5	26.2	372.9	2,175.7
382002671	29x1.5	26.2	386.3	2,194.0
382002672	30x1.5	26.2	399.6	2,212.4
382002673	31x1.5	27.0	412.9	2,300.9
382002674	32x1.5	27.0	426.2	2,319.3
382002675	33x1.5	27.0	439.5	2,337.6
382002676	34x1.5	27.9	452.9	2,431.7
382002677	35x1.5	27.9	466.2	2,450.1
382002678	36x1.5	27.9	479.5	2,468.5
382002679	37x1.5	27.9	492.8	2,486.8
382002680	38x1.5	28.9	506.1	2,561.0
382002681	39x1.5	28.9	519.5	2,579.4
382002682	40x1.5	28.9	532.8	2,597.7
382002683	41x1.5	30.3	546.1	2,728.8
382002684	42x1.5	30.3	559.4	2,747.1
382002685	43x1.5	30.3	572.7	2,765.5
382002686	44x1.5	31.3	586.1	2,866.2
382002687	45x1.5	31.3	599.4	2,884.6
382002688	46x1.5	31.3	612.7	2,903.0
382002689	47x1.5	31.3	626.0	2,921.3
382002690	48x1.5	31.8	639.3	2,968.1
382002691	49x1.5	31.8	652.6	2,986.5
382002692	50x1.5	31.8	666.0	3,004.8
382002693	51x1.5	31.8	679.3	3,023.2
382002694	52x1.5	32.6	692.6	3,112.5
382002695	53x1.5	32.6	705.9	3,130.9
382002696	54x1.5	32.6	719.2	3,149.3
382002697	55x1.5	32.6	732.6	3,167.6
382002698	56x1.5	32.6	745.9	3,186.0
382002699	57x1.5	32.6	759.2	3,204.4
382002700	58x1.5	32.6	772.5	3,222.7
382002701	59x1.5	32.6	785.8	3,241.1

Article number	Number of cores and mm ² per conductor	Nominal outer diameter (mm)	Copper weight (kg/km) Approx.	Weight (kg/km) Approx.
382002702	60x1.5	32.6	799.2	3,259.5
382002703	61x1.5	34.3	812.5	3,400.0
382002711	9x2.5	19.8	195.7	2,110.6
382002712	10x2.5	20.5	217.5	1,518.1
382002713	11x2.5	20.5	239.2	1,545.8
382002714	12x2.5	21.1	261.0	1,606.9
382002715	13x2.5	21.9	282.7	1,704.7
382002716	14x2.5	21.9	304.5	1,732.4
382002717	15x2.5	22.9	326.2	1,841.4
382002718	16x2.5	22.9	348.0	1,869.1
382002719	17x2.5	23.9	369.7	1,952.5
382002720	18x2.5	23.9	391.5	1,980.2
382002721	19x2.5	23.9	413.2	2,007.9
382002722	20x2.5	25.0	435.0	2,122.4
382002723	21x2.5	25.0	456.7	2,150.1
382002724	22x2.5	26.2	478.5	2,270.2
382002725	23x2.5	26.2	500.2	2,297.9
382002726	24x2.5	27.3	522.0	2,412.5
382002727	25x2.5	27.3	543.7	2,440.2
382002728	26x2.5	27.3	565.5	2,467.8
382002729	27x2.5	27.8	587.2	2,523.4
382002730	28x2.5	28.7	609.0	2,626.8
382002731	29x2.5	28.7	630.7	2,654.5
382002732	30x2.5	28.7	652.5	2,682.1
382002733	31x2.5	29.7	674.2	2,791.1
382002734	32x2.5	29.7	696.0	2,818.8
382002735	33x2.5	29.7	717.7	2,846.5
382002736	34x2.5	31.1	739.5	2,987.7
382002737	35x2.5	31.1	761.2	3,015.3
382002738	36x2.5	31.1	783.0	3,043.0
382002739	37x2.5	31.1	804.7	3,070.7
382002740	38x2.5	32.2	826.5	3,186.4
382002741	39x2.5	32.2	848.2	3,214.1
382002742	40x2.5	32.2	870.0	3,241.7
382002743	41x2.5	33.4	891.7	3,363.1
382002744	42x2.5	33.4	913.5	3,390.8
382002745	43x2.5	33.4	935.2	3,418.5
382002746	44x2.5	34.5	957.0	3,508.7
382002747	45x2.5	34.5	978.7	3,536.3
382002748	46x2.5	34.5	1000.5	3,564.0
382002749	47x2.5	34.5	1022.2	3,591.7
382002750	48x2.5	35.0	1044.0	3,673.3
382002751	49x2.5	35.0	1065.7	3,701.0
382002752	50x2.5	35.0	1087.5	3,728.6
382002753	51x2.5	35.0	1109.2	3,756.3
382002754	52x2.5	35.9	1131.0	3,860.7
382002755	53x2.5	35.9	1152.7	3,888.3
382002756	54x2.5	35.9	1174.5	3,916.0
382002757	55x2.5	35.9	1196.2	3,943.7
382002758	56x2.5	35.9	1218.0	3,971.3
382002759	57x2.5	35.9	1239.7	3,999.0
382002760	58x2.5	35.9	1261.5	4,026.7
382002761	59x2.5	35.9	1283.2	4,054.4
382002762	60x2.5	35.9	1305.0	4,082.0
382002763	61x2.5	37.9	1326.7	4,248.9
382002766	2x16	19.9	277.4	2,289.3
382002787	2x25	23.3	438.8	2,110.0
382002788	2x35	25.7	608.9	2,527.7
382002789	2x50	24.2	820.2	2,398.3
382002790	2x70	26.9	1184.4	2,983.3
382002791	2x95	29.3	1644.7	3,640.4
382002792	2x120	32.2	2074.6	4,313.5
382002793	2x150	35.3	2559.8	5,058.4
382002794	2x185	38.4	3203.0	5,995.1
382002795	2x240	42.4	4209.8	7,339.3
382002796	2x300	46.5	5281.5	8,790.9
382002797	2x400	51.6	6753.6	10,747.4
382002801	3x16	21.0	416.1	1,822.8
382002802	3x25	24.6	658.3	2,418.7
382002803	3x35	27.2	913.3	2,927.2
382002804	3x50	27.3	1230.3	3,061.2
382002805	3x70	31.6	1776.6	3,963.1
382002806	3x95	36.7	2467.0	5,062.4
382002807	3x120	38.4	3112.0	5,885.1
382002808	3x150	42.3	3839.7	6,956.0

ÖLFLEX® POWER LV 2X LSZH ARM

DS 382002644

valid from: 2018-03-31

Article number	Number of cores and mm ² per conductor	Nominal outer diameter (mm)	Copper weight (kg/km) Approx.	Weight (kg/km) Approx.
ÖLFLEX® POWER LV 2X LSZH ARM - RI2XHXS SAHX1BK				
382002809	3x185	46.3	4804.5	8,315.4
382002810	3x240	50.3	6314.7	10,195.2
382002811	3x300	54.7	7922.3	12,243.0
382002812	3x400	60.5	10130.4	15,038.2
382002813	3.5x25	24.7	797.0	2,416.4
382002814	3.5x35	26.7	1052.0	2,843.2
382002815	3.5x50	30.1	1449.7	3,516.0
382002816	3.5x70	33.6	2081.0	4,455.2
382002817	3.5x95	37.6	2877.1	5,579.1
382002818	3.5x120	41.7	3704.2	6,775.6
382002819	3.5x150	45.9	4431.9	7,896.6
382002820	3.5x185	51.8	5626.9	9,623.5
382002821	3.5x240	56.6	7352.0	11,838.6
382002822	3.5x300	59.3	9202.2	13,983.1
382002823	3.5x400	67.5	11731.9	17,405.0
382002826	4x10	20.0	348.7	1,654.4
382002827	4x16	22.7	554.8	2,106.4
382002828	4x25	26.8	877.7	2,853.5
382002829	4x35	29.7	1217.7	3,472.3
382002830	4x50	29.4	1640.4	3,668.8
382002831	4x70	33.6	2368.8	4,759.7
382002832	4x95	36.9	3289.3	5,943.2
382002833	4x120	40.8	4149.3	7,160.4
382002834	4x150	44.7	5119.7	8,499.2
382002835	4x185	49.5	6406.0	10,276.1
382002836	4x240	54.9	8419.6	12,803.3
382002837	4x300	60.3	10563.0	15,491.9
ÖLFLEX® POWER LV 2X LSZH ARM - RI2XSWAHX1BK				
382002764	1x4	10.8	34.6	1,293.1
382002765	1x6	11.4	51.8	1,415.6
382002766	1x10	12.3	87.2	1,615.1
382002767	1x16	13.4	138.7	1,517.5
382002768	1x25	15.1	219.4	1,853.9
382002769	1x35	16.3	304.4	1,830.5
382002770	1x50	17.6	410.1	2,103.2
ÖLFLEX® POWER LV 2X LSZH ARM - RI2XSSAHX1BK				
382002771	1x70	19.0	592.2	2,385.4
382002772	1x95	20.9	822.3	2,095.8
382002773	1x120	22.6	1037.3	2,436.9
382002774	1x150	24.5	1279.9	2,848.4
382002775	1x185	26.8	1601.5	3,364.3
382002776	1x240	29.9	2104.9	4,112.9
382002777	1x300	32.6	2640.8	4,867.4
382002778	1x400	36.1	3376.8	5,913.3
382002779	1x500	40.5	4336.3	7,252.5
382002780	1x630	44.5	5608.1	8,870.9
382002781	1x800	49.6	7181.4	10,928.7
382002782	1x1000	54.6	9017.6	13,207.6
ÖLFLEX® POWER LV 2X LSZH ARM - RI2XHXS WAHXUVAR1BK				
382002838	2x1.5	13.7	26.6	1,475.8
382002839	3x1.5	14.2	40.0	1,575.2
382002840	4x1.5	15.0	53.3	1,704.4
382002841	5x1.5	15.8	66.6	1,847.6
382002842	6x1.5	16.7	79.9	1,684.2
382002843	7x1.5	16.7	93.2	1,702.6
382002844	8x1.5	18.1	106.6	1,894.9
382002845	9x1.5	19.1	119.9	2,048.1
382002846	10x1.5	20.1	133.2	1,460.6
382002847	11x1.5	20.1	146.5	1,478.9
382002898	2x2.5	14.5	43.5	1,621.6
382002899	3x2.5	15.1	65.2	1,741.9
382002900	4x2.5	15.9	87.0	1,879.0
382002901	5x2.5	16.9	108.7	1,782.7
382002902	6x2.5	17.9	130.5	1,894.5
382002903	7x2.5	17.9	152.2	1,922.1
382002904	8x2.5	19.9	174.0	2,176.2
382002977	2x4	15.5	69.2	1,815.8
382002978	2x6	16.7	103.6	1,750.5
382002979	2x10	18.5	174.3	2,074.5
382002992	3x4	16.1	103.8	1,934.6
382002993	3x6	17.4	155.4	1,894.7
382002994	3x10	19.8	261.5	2,293.9
382003018	4x4	17.2	138.4	1,843.7
382003019	4x6	18.6	207.2	2,103.2

Article number	Number of cores and mm ² per conductor	Nominal outer diameter (mm)	Copper weight (kg/km) Approx.	Weight (kg/km) Approx.
ÖLFLEX® POWER LV 2X LSZH ARM - RI2XHXS SAHXUVAR1BK				
382002848	12x1.5	19.0	159.8	2,022.3
382002849	13x1.5	20.2	173.2	1,463.4
382002850	14x1.5	20.2	186.5	1,481.7
382002851	15x1.5	21.0	199.8	1,544.7
382002852	16x1.5	21.0	213.1	1,563.1
382002853	17x1.5	21.9	226.4	1,657.2
382002854	18x1.5	21.9	239.7	1,675.6
382002855	19x1.5	21.9	253.1	1,693.9
382002856	20x1.5	22.9	266.4	1,793.6
382002857	21x1.5	22.9	279.7	1,812.0
382002858	22x1.5	23.9	293.0	1,886.1
382002859	23x1.5	23.9	306.3	1,904.5
382002860	24x1.5	24.9	319.7	2,004.2
382002861	25x1.5	24.9	333.0	2,022.5
382002862	26x1.5	24.9	346.3	2,040.9
382002863	27x1.5	25.4	359.6	2,112.7
382002864	28x1.5	26.2	372.9	2,175.7
382002865	29x1.5	26.2	386.3	2,194.0
382002866	30x1.5	26.2	399.6	2,212.4
382002867	31x1.5	27.0	412.9	2,300.9
382002868	32x1.5	27.0	426.2	2,319.3
382002869	33x1.5	27.0	439.5	2,337.6
382002870	34x1.5	27.9	452.9	2,431.7
382002871	35x1.5	27.9	466.2	2,450.1
382002872	36x1.5	27.9	479.5	2,468.5
382002873	37x1.5	27.9	492.8	2,486.8
382002874	38x1.5	28.9	506.1	2,561.0
382002875	39x1.5	28.9	519.5	2,579.4
382002876	40x1.5	28.9	532.8	2,597.7
382002877	41x1.5	30.3	546.1	2,728.8
382002878	42x1.5	30.3	559.4	2,747.1
382002879	43x1.5	30.3	572.7	2,765.5
382002880	44x1.5	31.3	586.1	2,866.2
382002881	45x1.5	31.3	599.4	2,884.6
382002882	46x1.5	31.3	612.7	2,903.0
382002883	47x1.5	31.3	626.0	2,921.3
382002884	48x1.5	31.8	639.3	2,968.1
382002885	49x1.5	31.8	652.6	2,986.5
382002886	50x1.5	31.8	666.0	3,004.8
382002887	51x1.5	31.8	679.3	3,023.2
382002888	52x1.5	32.6	692.6	3,112.5
382002889	53x1.5	32.6	705.9	3,130.9
382002890	54x1.5	32.6	719.2	3,149.3
382002891	55x1.5	32.6	732.6	3,167.6
382002892	56x1.5	32.6	745.9	3,186.0
382002893	57x1.5	32.6	759.2	3,204.4
382002894	58x1.5	32.6	772.5	3,222.7
382002895	59x1.5	32.6	785.8	3,241.1
382002896	60x1.5	32.6	799.2	3,259.5
382002897	61x1.5	34.3	812.5	3,400.0
382002905	9x2.5	19.8	195.7	2,110.6
382002906	10x2.5	20.5	217.5	1,518.1
382002907	11x2.5	20.5	239.2	1,545.8
382002908	12x2.5	21.1	261.0	1,606.9
382002909	13x2.5	21.9	282.7	1,704.7
382002910	14x2.5	21.9	304.5	1,732.4
382002911	15x2.5	22.9	326.2	1,841.4
382002912	16x2.5	22.9	348.0	1,869.1
382002913	17x2.5	23.9	369.7	1,952.5
382002914	18x2.5	23.9	391.5	1,980.2
382002915	19x2.5	23.9	413.2	2,007.9
382002916	20x2.5	25.0	435.0	2,122.4
382002917	21x2.5	25.0	456.7	2,150.1
382002918	22x2.5	26.2	478.5	2,270.2
382002919	23x2.5	26.2	500.2	2,297.9
382002920	24x2.5	27.3	522.0	2,412.5
382002921	25x2.5	27.3	543.7	2,440.2
382002922	26x2.5	27.3	565.5	2,467.8
382002923	27x2.5	27.8	587.2	2,523.4
382002924	28x2.5	28.7	609.0	2,626.8
382002925	29x2.5	28.7	630.7	2,654.5
382002926	30x2.5	28.7	652.5	2,682.1
382002927	31x2.5	29.7	674.2	2,791.1
382002928	32x2.5	29.7	696.0	2,818.8

ÖLFLEX® POWER LV 2X LSZH ARM
DS 382002644

valid from: 2018-03-31

Article number	Number of cores and mm ² per conductor	Nominal outer diameter (mm)	Copper weight (kg/km) Approx.	Weight (kg/km) Approx.
ÖLFLEX® POWER LV 2X LSZH ARM - RI2XHXS SAHXUVAR 1BK				
382002929	33x2.5	29.7	717.7	2,846.5
382002930	34x2.5	31.1	739.5	2,987.7
382002931	35x2.5	31.1	761.2	3,015.3
382002932	36x2.5	31.1	783.0	3,043.0
382002933	37x2.5	31.1	804.7	3,070.7
382002934	38x2.5	32.2	826.5	3,186.4
382002935	39x2.5	32.2	848.2	3,214.1
382002936	40x2.5	32.2	870.0	3,241.7
382002937	41x2.5	33.4	891.7	3,363.1
382002938	42x2.5	33.4	913.5	3,390.8
382002939	43x2.5	33.4	935.2	3,418.5
382002940	44x2.5	34.5	957.0	3,508.7
382002941	45x2.5	34.5	978.7	3,536.3
382002942	46x2.5	34.5	1000.5	3,564.0
382002943	47x2.5	34.5	1022.2	3,591.7
382002944	48x2.5	35.0	1044.0	3,673.3
382002945	49x2.5	35.0	1065.7	3,701.0
382002946	50x2.5	35.0	1087.5	3,728.6
382002947	51x2.5	35.0	1109.2	3,756.3
382002948	52x2.5	35.9	1131.0	3,860.7
382002949	53x2.5	35.9	1152.7	3,888.3
382002950	54x2.5	35.9	1174.5	3,916.0
382002951	55x2.5	35.9	1196.2	3,943.7
382002952	56x2.5	35.9	1218.0	3,971.3
382002953	57x2.5	35.9	1239.7	3,999.0
382002954	58x2.5	35.9	1261.5	4,026.7
382002955	59x2.5	35.9	1283.2	4,054.4
382002956	60x2.5	35.9	1305.0	4,082.0
382002957	61x2.5	37.9	1326.7	4,248.9
382002980	2x16	19.9	277.4	2,289.3
382002981	2x25	23.3	438.8	2,110.0
382002982	2x35	25.7	608.9	2,527.7
382002983	2x50	24.2	820.2	2,398.3
382002984	2x70	26.9	1184.4	2,983.3
382002985	2x95	29.3	1644.7	3,640.4
382002986	2x120	32.2	2074.6	4,313.5
382002987	2x150	35.3	2559.8	5,058.4
382002988	2x185	38.4	3203.0	5,995.1
382002989	2x240	42.4	4209.8	7,339.3
382002990	2x300	46.5	5281.5	8,790.9
382002991	2x400	51.6	6753.6	10,747.4
382002995	3x16	21.0	416.1	1,822.8
382002996	3x25	24.6	658.3	2,418.7
382002997	3x35	27.2	913.3	2,927.2
382002998	3x50	27.3	1230.3	3,061.2
382002999	3x70	31.6	1776.6	3,963.1
382003000	3x95	36.7	2467.0	5,062.4
382003001	3x120	38.4	3112.0	5,885.1
382003002	3x150	42.3	3839.7	6,956.0
382003003	3x185	46.3	4804.5	8,315.4
382003004	3x240	50.3	6314.7	10,195.2
382003005	3x300	54.7	7922.3	12,243.0
382003006	3x400	60.5	10130.4	15,038.2
382003007	3.5x25	24.7	797.0	2,416.4
382003008	3.5x35	26.7	1052.0	2,843.2
382003009	3.5x50	30.1	1449.7	3,516.0
382003010	3.5x70	33.6	2081.0	4,455.2
382003011	3.5x95	37.6	2877.1	5,579.1
382003012	3.5x120	41.7	3704.2	6,775.6
382003013	3.5x150	45.9	4431.9	7,896.6
382003014	3.5x185	51.8	5626.9	9,623.5
382003015	3.5x240	56.6	7352.0	11,838.6
382003016	3.5x300	59.3	9202.2	13,983.1
382003017	3.5x400	67.5	11731.9	17,405.0
382003020	4x10	20.0	348.7	1,654.4
382003021	4x16	22.7	554.8	2,106.4
382003022	4x25	26.8	877.7	2,853.5
382003023	4x35	29.7	1217.7	3,472.3
382003024	4x50	29.4	1640.4	3,668.8
382003025	4x70	33.6	2368.8	4,759.7
382003026	4x95	36.9	3289.3	5,943.2
382003027	4x120	40.8	4149.3	7,160.4
382003028	4x150	44.7	5119.7	8,499.2

Article number	Number of cores and mm ² per conductor	Nominal outer diameter (mm)	Copper weight (kg/km) Approx.	Weight (kg/km) Approx.
382003029	4x185	49.5	6406.0	10,276.1
382003030	4x240	54.9	8419.6	12,803.3
382003031	4x300	60.3	10563.0	15,491.9
ÖLFLEX® POWER LV 2X LSZH ARM - RI2XSWAHXUVAR 1BK				
382002958	1x4	10.8	34.6	1,293.1
382002959	1x6	11.4	51.8	1,415.6
382002960	1x10	12.3	87.2	1,615.1
382002961	1x16	13.4	138.7	1,517.5
382002962	1x25	15.1	219.4	1,853.9
382002963	1x35	16.3	304.4	1,830.5
382002964	1x50	17.6	410.1	2,103.2
ÖLFLEX® POWER LV 2X LSZH ARM - RI2XSSAHXUVAR 1BK				
382002965	1x70	19.0	592.2	2,385.4
382002966	1x95	20.9	822.3	2,095.8
382002967	1x120	22.6	1037.3	2,436.9
382002968	1x150	24.5	1279.9	2,848.4
382002969	1x185	26.8	1601.5	3,364.3
382002970	1x240	29.9	2104.9	4,112.9
382002971	1x300	32.6	2640.8	4,867.4
382002972	1x400	36.1	3376.8	5,913.3
382002973	1x500	40.5	4336.3	7,252.5
382002974	1x630	44.5	5608.1	8,870.9
382002975	1x800	49.6	7181.4	10,928.7
382002976	1x1000	54.6	9017.6	13,207.6
ÖLFLEX® POWER LV 2X LSZH ARM - RI2XWAhX1BK				
382003108	1x4	10.8	34.6	1,213.9
382003109	1x6	11.4	51.8	1,328.5
382003110	1x10	12.3	87.2	1,512.2
382003111	1x16	13.4	138.7	1,390.8
382003112	1x25	15.1	219.4	1,695.5
382003113	1x35	16.3	304.4	1,656.3
382003114	1x50	17.6	410.1	1,905.3
382003115	1x70	20.6	592.2	1,689.3
382003116	1x95	22.5	822.3	2,043.9
382003117	1x120	24.2	1037.3	2,382.2
382003118	1x150	26.1	1279.9	2,759.8
382003119	1x185	28.4	1601.5	3,253.1
382003120	1x240	31.5	2104.9	3,980.7
382003121	1x300	35.0	2640.8	4,832.9
382003122	1x400	38.5	3376.8	5,846.7
382003123	1x500	42.9	4336.3	7,174.2
382003124	1x630	47.3	5608.1	8,818.5
382003125	1x800	53.2	7181.4	11,027.6
382003126	1x1000	58.4	9017.6	13,348.1
ÖLFLEX® POWER LV 2X LSZH ARM - RI2XWAhXUVAR 1BK				
382003127	1x4	10.8	34.6	1,213.9
382003128	1x6	11.4	51.8	1,328.5
382003129	1x10	12.3	87.2	1,512.2
382003130	1x16	13.4	138.7	1,390.8
382003131	1x25	15.1	219.4	1,695.5
382003132	1x35	16.3	304.4	1,656.3
382003133	1x50	17.6	410.1	1,905.3
382003134	1x70	20.6	592.2	1,689.3
382003135	1x95	22.5	822.3	2,043.9
382003136	1x120	24.2	1037.3	2,382.2
382003137	1x150	26.1	1279.9	2,759.8
382003138	1x185	28.4	1601.5	3,253.1
382003139	1x240	31.5	2104.9	3,980.7
382003140	1x300	35.0	2640.8	4,832.9
382003141	1x400	38.5	3376.8	5,846.7
382003142	1x500	42.9	4336.3	7,174.2
382003143	1x630	47.3	5608.1	8,818.5
382003144	1x800	53.2	7181.4	11,027.6
382003145	1x1000	58.4	9017.6	13,348.1