



# EPIC<sup>®</sup> Newsletter

Edition June 2008

Page 1 of 2

U.I. Lapp GmbH · Schulze-Delitzsch-Straße 25, 70565 Stuttgart, Tel.: +49 (0)711/78 38-01, Fax: +49 (0)711/78 38-26 40, [www.lappkabel.de](http://www.lappkabel.de)

---

## EPIC<sup>®</sup> H-BE inserts in new design with new features

The EPIC<sup>®</sup> H-BE inserts have been redesigned. In the new over moulding tools there are a lot of ideas and suggestions of the customer implemented. The technical data's are unchanged.

### The most important new features are:

- New transportation safety device
- Major diameter of the screw hole, fits for US screw drivers with thicker shaft
- Combination screw for Phillips head PH1 and slit 3,5 x 0,6mm, Tightening torque 0,5Nm
- Contact numbers are integrated in the insulator body, the higher numbers are also integrated
- PE-contacts with treat on both sides of the insert.  
The PE screw is mounted nearby PIN 1.

The article numbers of the affected inserts will remain unchanged. The changing of the products is step by step. Because of the diversity and the different articles range of stock the deliveries can be mixed. The production starts in middle of June.

### **Safety note:**

When connecting the PE wire, it is important to ensure a low resistance electrical connection with the counterpart. When changing the PE screw, make sure this is done on both sides to ensure the electrical safety. The application can be used in conductive housing, or it may protect an internal conductor.

Also you have to follow the national safety rules e.g. EN 50110-1



# EPIC<sup>®</sup> Newsletter

Edition June 2008

Page 2 of 2

U.I. Lapp GmbH · Schulze-Delitzsch-Straße 25, 70565 Stuttgart, Tel.: +49 (0)711/78 38-01, Fax: +49 (0)711/78 38-26 40, [www.lappkabel.de](http://www.lappkabel.de)

## Product details

- Screws PH1
- Major diameter for screwdrivers
- Numbering injected
- Transportation safety device
- PE on both sides

