

CABLE TRACK FORMAT

Application Information: _____

Type of Mounting: Center or Off-Center: Distance: _____" Travel Length (Ls): _____"

Unsupported length: (CM = Ls/2, OCM = Ls): _____"

Mounting Sketch

Item #	A Part Number	B Quantity	C Nominal Diameter	D Min. Radius Factor	E Min. Radius	F Clearances Factor - Min.	G Min. Clearance (G * B)	H Weight (Lbs./ft) x B
1			"		"		"	
2			"		"		"	
3			"		"		"	
4			"		"		"	
5			"		"		"	
6			"		"		"	
7			"		"		"	
8	Dividers - Vert.		"				"	
Total:							"	Lbs./ft

Min. Inside Height (Largest Nominal Diameter of C): _____" x 1.20 % = _____"

Min. Radius: _____" (Largest radius of E) Min. Width: _____" (Total of G) Weight: _____ Lbs./ft. (Total of H) Track chosen: _____ (Smallest Model / Type chosen)

Cable Track Layout Sketch

(From Catalog Based on Track chosen)

Inside Height: _____" Outside Height: _____" Inside Width: _____" Outside Width: _____" Bend Radius: _____"

Do all the characteristics of the selected track match the application requirements?

Center Mounting Formula (CM): Calculate Track Length & Links needed

$$CM = (Ls / 2) + Lb \text{ (Loop Length)} \qquad \# \text{ of links} = CM / t \text{ (Link Length)}$$

$$= \underline{\hspace{2cm}} \text{ inches} \qquad = \underline{\hspace{2cm}} \text{ (round up)} = \underline{\hspace{2cm}} \text{ links}$$

Off-Center Mounting Formula (OCM): Calculate Track Length & Links needed

$$OCM = (Ls / 2) + \text{Off-center} + Lb \text{ (Loop Length)} \qquad \# \text{ of links} = OCM / t \text{ (Link Length)}$$

$$= \underline{\hspace{2cm}} \text{ inches} \qquad = \underline{\hspace{2cm}} \text{ (round up)} = \underline{\hspace{2cm}} \text{ links}$$

of Dividers: (#of links / 2, rounded up)*(Dividers per link) _____

Order Track Part Number: _____

Comments: _____



LAPP USA
29 Hanover Road
Florham Park, NJ 07932
800-774-3539

LAPP CANADA
3505 Laird Road, Unit 10
Mississauga, Ontario L5L 5Y7
877-799-5277

LAPP MEXICO
Metalurgia 2730
Alamo Industrial, C.P. 44490
800-024-5277