

EPIC® Pin & Sleeve Connectors

Selection Chart: International Standards

Dimensional Drawings Page 461				Male Plugs				
16A	# of Wires	# of Poles	Ground-Clock Position	IP 67	IP 44	IP 44	IP 67	IP 44
				Part #	Part #	Part #	Part #	Part #
110 - 130	3	2+PE	4	477203	700124	477202	475203	475202
	4	3+PE	4	477213	700134	477212	475213	475212
	5	3+N+PE	4	477223	700144	477222	475223	475222
200 - 250	3	2+PE	6	477303	700126	477302	475303	475302
	4	3+PE	9	477313	700139	477312	475313	475312
	5	3+N+PE	9	477323	700149	477322	475323	475322
380 - 415	3	2+PE	9	477403	700129	477402	475403	475402
	4	3+PE	6	477413	700136	477412	475413	475412
	5	3+N+PE	6	477423	700146	477422	475423	475422
480 - 500	3	2+PE	7	477273	700127	477502	NA	NA
	4	3+PE	7	477513	700137	477512	475513	475512
	5	3+N+PE	7	477523	700147	477522	475523	475522
600 - 690	4	3+PE	5	NA	700135	NA	NA	NA
	5	3+N+PE	5	NA	700145	NA	NA	NA
440 - 460	4	3+PE	11	477453	700131	477452	475453	475452
	5	3+N+PE	11	477533	700141	477532	475533	475532

Please Note that
Dimensional Drawings
are on the page
indicated on the chart

Dimensions are the same
for North American and
International Standards.

Male Plugs mate with
Female connectors, panel
mounted receptacles, &
switched socket outlets.
Male Plug Inlets mate with
female connectors.

16A			Female Connectors Page 462		Female Receptacles Page 462			Male Inlets Page 463	
			IP 67	IP 44	IP 67	IP 44	IP 44	IP 67	IP 44
#	Poles	Ground	Part #	Part #	Part #	Part #	Part #	Part #	Part #
3	2+PE	4	473203	720124	471263	431611	471262	476203	476202
4	3+PE	4	473213	720134	471273	441611	471272	476213	476212
5	3+N+PE	4	473223	720144	471223	451611	471222	476223	476222
3	2+PE	6	473303	720126	471363	431622	471362	476303	476302
4	3+PE	9	473313	720139	471373	441622	471372	476313	476312
5	3+N+PE	9	473323	720149	471333	451622	471332	476323	476322
3	2+PE	9	473403	720129	471463	431638	471462	476403	476402
4	3+PE	6	473413	720136	471473	441638	471472	476413	476412
5	3+N+PE	6	473423	720146	471483	451638	471482	476423	476422
3	2+PE	7	473503	720127	471553	431650	471552	NA	NA
4	3+PE	7	473513	720137	471573	441650	471572	476513	476512
5	3+N+PE	7	473523	720147	471563	451650	471562	476523	476522
4	3+PE	5	NA	720135	NA	NA	NA	NA	NA
5	3+N+PE	5	NA	720145	NA	NA	NA	NA	NA
4	3+PE	11	473463	720131	471583	441644	471582	476453	476452
5	3+N+PE	11	473533	720141	471593	451644	471592	476533	476532

EPIC® Pin & Sleeve Connectors

Selection Chart: International Standards

Dimensional Drawings Page 464				IP 67 	IP 44 	IP 44 
32A	Wires	Poles	Ground	Part #	Part #	Part #
110 - 130	3	2+PE	4	477206	700224	477205
	4	3+PE	4	477216	700234	477215
	5	3+N+PE	4	477226	700244	477225
200 - 250	3	2+PE	6	477306	700226	477305
	4	3+PE	9	477316	700239	477315
	5	3+N+PE	9	477326	700249	477325
380 - 415	3	2+PE	9	477406	700229	477405
	4	3+PE	6	477416	700236	477415
	5	3+N+PE	6	477426	700246	477425
480 - 500	3	2+PE	7	477556	700227	477505
	4	3+PE	7	477516	700237	477515
	5	3+N+PE	7	477526	700247	477525
600 - 690	4	3+PE	5	NA	700235	NA
	5	3+N+PE	5	NA	700245	NA
440 - 460	4	3+PE	11	477456	700231	477455
	5	3+N+PE	11	477536	700241	477535

Please Note that
Dimensional Drawings
are on the page
indicated on the chart

Dimensions are the same
for North American and
International Standards.

Male Plugs mate with
Female connectors, panel
mounted receptacles, &
switched socket outlets.
Male Plug Inlets mate with
female connectors.

32A			Female Connectors Page 464		Female Receptacles Page 465			Male Inlets Page 466	
			IP 67 	IP 44 	IP 67 	IP 44 	IP 44 	IP 67 	IP 44 
#	Poles	Ground	Part #	Part #	Part #	Part #	Part #	Part #	Part #
3	2+PE	4	473206	720224	471267	433211	471266	476206	476205
4	3+PE	4	473216	720234	471277	443211	471276	476216	476215
5	3+N+PE	4	473226	720244	471287	453211	471286	476226	476225
3	2+PE	6	473306	720226	471367	433222	471366	476306	476305
4	3+PE	9	473316	720239	471377	443222	471376	476316	476315
5	3+N+PE	9	473326	720249	471387	453222	471386	476326	476325
3	2+PE	9	473406	720229	471467	433238	471466	476406	476405
4	3+PE	6	473416	720236	471477	443238	471476	476416	476415
5	3+N+PE	6	473426	720246	471487	453238	471486	476426	476425
3	2+PE	7	473506	720227	471556	433250	471555	NA	NA
4	3+PE	7	473516	720237	471577	443250	471576	476516	476515
5	3+N+PE	7	473526	720247	471567	453250	471566	476526	476525
4	3+PE	5	NA	720235	NA	NA	NA	NA	NA
5	3+N+PE	5	NA	720245	NA	NA	NA	NA	NA
4	3+PE	11	473466	720231	471587	443244	471586	476456	476455
5	3+N+PE	11	473536	720241	471597	453244	471596	476536	476535

EPIC® Pin & Sleeve Connectors

Selection Chart: International Standards

				Page 463		Page 466	
				ULYSEE IP 66/67 	16A ALUPRES IP 65 	ULYSEE IP 66/67 	32A ALUPRES IP 65 
	# of Wires	Poles	Ground-Clock Position	with Fuse Holder	Direct Connect	with Fuse Holder	Direct Connect
				Part #	Part #	Part #	Part #
110 - 130	3	2+PE	4	400124	460124	400224	460224
	4	3+PE	4	400134	NA	400234	NA
	5	3+N+PE	4	400144	NA	400244	NA
200 - 250	3	2+PE	6	400126	460126	400226	460226
	4	3+PE	9	400139	460139	400239	460239
	5	3+N+PE	9	400149	NA	400249	460249
380 - 415	3	2+PE	9	400129	NA	400229	460229
	4	3+PE	6	400136	460136	400236	460236
	5	3+N+PE	6	400146	460146	400246	460246
480 - 500	4	3+PE	7	400137	NA	400237	460237
	5	3+N+PE	7	400147	NA	400247	460247
440 - 460	4	3+PE	11	400131	NA	400231	460231
	5	3+N+PE	11	400141	NA	400241	460241

Please Note that Dimensional Drawings are on the page indicated on the chart

Dimensions are the same for North American and International Standards.

			Page 463		Page 467		Page 468		
63A			IP 67 	IP 67 	IP 67 	IP 67 	IP 67 	IP 66/67 w/fuse holder 	IP 55 Direct Connect 
#	Poles	Clock Position	Part #	Part #	Part #	Part #	Part #	Part #	Part #
3	2+PE	4	477207	473207	536311	436311	476207	400324	NA
4	3+PE	4	477217	473217	546311	446311	476217	400334	NA
5	3+N+PE	4	477227	473227	556311	456311	476227	400344	NA
3	2+PE	6	477307	473307	536322	436322	476307	400326	460326
4	3+PE	9	477317	473317	546322	446322	476317	400339	460339
5	3+N+PE	9	477327	473327	556322	456322	476327	400349	460349
3	2+PE	9	477407	473407	536338	436338	476407	400329	460329
4	3+PE	6	477417	346338	546338	446338	746338	400336	NA
5	3+N+PE	6	477427	356338	556338	456338	756338	400346	NA
4	3+PE	7	477517	346350	546350	446350	476517	400337	460337
4	3+PE	11	477457	473467	546344	446344	476457	400331	460331
5	3+N+PE	11	477537	473537	556344	456344	476537	400341	460341

			Page 469				Page 470
125A			IP 67 	IP 67 	IP 67 	IP 67 	IP 67 
#	Poles	Clock Position	Part #	Part #	Part #	Part #	Part #
4	3+PE	4	477218	473218	549311	449311	476218
5	3+N+PE	4	477228	473228	559311	459311	476228
4	3+PE	9	477318	473318	549322	449322	476318
5	3+N+PE	9	477328	473328	559322	459322	476328
4	3+PE	6	249538	349538	549538	449538	749538
5	3+N+PE	6	259538	359538	559538	459538	759538
4	3+PE	7	249550	349550	549550	449550	749550
4	3+PE	11	477458	473468	549344	449344	476458
5	3+N+PE	11	477538	473538	559344	459344	476538

Male plugs mate with female connectors, panel mounted receptacles, & switched socket outlets. Male plug inlets mate with female connectors.