

Cable entries at a glance

ÖLFLEX®
UNITRONIC®
ETHERLINE®
HITRONIC®
EPIC®
SKINTOP®
SILVYN®
FLEXIMARK®
ACCESSORIES
APPENDIX

Usage criteria	Cable entries																													
Page	773	763	689	698	690	687	691	703	722	724	714	712	694	775	764	709	697	710	702	704	767	777	701	766	721	692	771	763	684	693
	SKINTOP® BS	SKINTOP® BS NPT	SKINTOP® BS-M/ISO	SKINTOP® BS(R)-M METAL	SKINTOP® BT/BT-M	SKINTOP® CLICK/CLICK-R	SKINTOP® CLICK BS	SKINTOP® COLD/COLD-R	SKINTOP® CUBE	SKINTOP® CUBE MULTI	SKINTOP® HYGIENIC/HYGIENIC-R	SKINTOP® INOX/INOX-R	SKINTOP® K(R)-M ATEX PLUS/PLUS BLUE	SKINTOP® MS(R)	SKINTOP® MS(R) NPT	SKINTOP® MS(R)-M ATEX/XL	SKINTOP® MS(R)-M/XL	SKINTOP® MS-M BRUSH ATEX	SKINTOP® MS-M BRUSH/BRUSH plus	SKINTOP® MS-IS-M	SKINTOP® MS-NPT BRUSH	SKINTOP® MS-SC	SKINTOP® MS-SC-M	SKINTOP® MS-SC NPT	SKINTOP® MULTI	SKINTOP® SOLAR/SOLAR plus	SKINTOP® ST(R)	SKINTOP® ST(R) NPT	SKINTOP® ST(R)-M/ISO	SKINTOP® ST-HF-M
Properties																														
IP protection rating	68	68	68	68	68	68	68	68	64	66	68	68	68	68	68	68	68	68	68	68	68	68	68	68	68	68	68	68	68	68
NEMA protection rating*																														
Metric connection thread																														
PG connection thread																														
NPT connection thread																														
For round cables																														
For flat cables																														
Metal																														
Plastic																														
Angled																														
Strain relief																														
Vibration protection																														
Anti-kink protection																														
Screening connection																														
Suitable for Ex safety area																														
Halogen-free																														
Approval																														
ATEX																														
CSA																														
cULus																														
cURus																														
DNV																														
ECOLAB																														
EHEDG																														
TÜV																														
UL																														
UR																														
VDE																														

* covered sizes and cord diameters on request

Usage criteria	Cable entries																																			
Page	739	785	740	738	797	740	742	786	794	792	734	737	736	737	787	731	788	789	730	790	793	735	732	791	733	783	729	782	726	782	726	727	727	750		
	SKINDICHT® CN/CN-M	SKINDICHT® FL	SKINDICHT® KW-M	SKINDICHT® MINI	SKINDICHT® RWV	SKINDICHT® RWV-M	SKINDICHT® SE/SEM	SKINDICHT® SH	SKINDICHT® SHV	SKINDICHT® SHVE	SKINDICHT® SHVE-M	SKINDICHT® SHVE-M ATEX	SKINDICHT® SHV-FKM	SKINDICHT® SHV-M	SKINDICHT® SHV-M-FKM	SKINDICHT® SHZ	SKINDICHT® SHZ-M	SKINDICHT® SK	SKINDICHT® SKZ	SKINDICHT® SKZ-M	SKINDICHT® SR	SKINDICHT® SRE	SKINDICHT® SRE-M	SKINDICHT® SR-M	SKINDICHT® SR-SV	SKINDICHT® SR-SV-M	SKINDICHT® SVFK	SKINDICHT® SVF/SVF-M	SKINDICHT® SVRE	SKINDICHT® SVRE-M	SKINDICHT® SVRN	SKINDICHT® SVRN-M	SKINDICHT® SVRX-W	SKINDICHT® SVRX-Z	SKINDICHT® VENT	
Properties																																				
IP protection rating	68	65	55	68	55	55	55	20	68	68	68	68	68	68	55	55	20	55	55	65	65	65	65	65	65	54	54	54	54	54	54	54	54	68		
Metric connection thread																																				
PG connection thread																																				
NPT connection thread																																				
For round cables																																				
For flat cables																																				
Metal																																				
Plastic																																				
Angled																																				
Strain relief																																				
Vibration protection																																				
Anti-kink protection																																				
Screening connection																																				
Suitable for Ex safety area																																				
Halogen-free																																				