



Certificate type			EAC
Product	Page	Fire protection	EAC
<b>Flexible power and control cables, nominal voltage up to 500 V</b>			
ÖLFLEX® CLASSIC 100 300/500 V	27	✓	✓
ÖLFLEX® CLASSIC 100 CY	31	✓	✓
ÖLFLEX® CLASSIC 100 SY	32	✓	✓
ÖLFLEX® SMART 108	34	✓	✓
ÖLFLEX® CLASSIC 110	35	✓	✓
ÖLFLEX® CLASSIC 110 LT	39	✓	✓
ÖLFLEX® CLASSIC 110 Orange	40	✓	✓
ÖLFLEX® CLASSIC 110 CY	41	✓	✓
ÖLFLEX® CLASSIC 110 SY	42	✓	✓
ÖLFLEX® CLASSIC 115 CY	45	✓	✓
ÖLFLEX® EB	47	✓	✓
ÖLFLEX® EB CY	48	✓	✓
ÖLFLEX® 140	49	✓	✓
ÖLFLEX® 140 CY	50	✓	✓
ÖLFLEX® 150	51	✓	✓
ÖLFLEX® 150 CY	52	✓	✓
ÖLFLEX® 191	53	✓	✓
ÖLFLEX® 191 CY	54	✓	✓
ÖLFLEX® SF	59	✓	✓
ÖLFLEX® ROBUST 210	71		✓
ÖLFLEX® ROBUST 215 C	72		✓
ÖLFLEX® CLASSIC 400 P	73		✓
ÖLFLEX® CLASSIC 400 CP	74		✓
ÖLFLEX® CLASSIC 415 CP	75		✓
ÖLFLEX® 408 P	76		✓
ÖLFLEX® 409 P	77	✓	✓
ÖLFLEX® 440 P	78	✓	✓
ÖLFLEX® 440 CP	79	✓	✓
ÖLFLEX® 450 P	80	✓	✓
ÖLFLEX® 500 P	81	✓	✓
ÖLFLEX® 540 P	82	✓	✓
ÖLFLEX® 540 CP	83	✓	✓
ÖLFLEX® 550 P	84		✓
ÖLFLEX® SERVO FD 798 CP	111	✓	
Special Encoder and resolver cables	117	✓	✓
ÖLFLEX® CLASSIC FD 810	118	✓	✓
ÖLFLEX® CLASSIC FD 810 CY	119	✓	✓
ÖLFLEX® CHAIN 809	124	✓	✓
ÖLFLEX® CHAIN 809 CY	125	✓	✓
ÖLFLEX® CLASSIC FD 810 P	131	✓	✓
ÖLFLEX® CLASSIC FD 810 CP	132	✓	✓
ÖLFLEX® FD 855 P	140	✓	✓
ÖLFLEX® FD 855 CP	141	✓	✓
ÖLFLEX® ROBUST FD	133		✓
ÖLFLEX® ROBUST FD C	134		✓
ÖLFLEX® FD 891	127	✓	✓

Certificate type			EAC
Product	Page	Fire protection	EAC
ÖLFLEX® FD 891 CY	128	✓	✓
ÖLFLEX® FD 891 P	139	✓	✓
ÖLFLEX® PETRO FD 865 CP	142	✓	✓
ÖLFLEX® ROBOT 900 P	144	✓	✓
ÖLFLEX® ROBOT 900 DP	145	✓	✓
ÖLFLEX® ROBOT F1	146	✓	✓
ÖLFLEX® ROBOT F1 C	147	✓	✓
ÖLFLEX® SPIRAL 400 P	252		✓
ÖLFLEX® SPIRAL 540 P	255	✓	✓
<b>Flexible power and control cables, nominal voltage up to 750 V</b>			
ÖLFLEX® CLASSIC 100 450/750 V	29	✓	✓
ÖLFLEX® CLASSIC 100 Yellow	30	✓	✓
ÖLFLEX® CLASSIC 100 CY	31	✓	✓
ÖLFLEX® CLASSIC 100 SY	32	✓	✓
ÖLFLEX® ROBUST 200	70		✓
ÖLFLEX® 540 P	82	✓	✓
ÖLFLEX® 540 CP	83	✓	✓
ÖLFLEX® 550 P	84		✓
SERVO cables in acc. to SEW® Standard	248	✓	✓
ÖLFLEX® SPIRAL 540 P	255	✓	✓
<b>Flexible power and control cables, nominal voltage up to 1000 V</b>			
ÖLFLEX® CLASSIC 100 BK 0,6/1 kV	33	✓	✓
ÖLFLEX® CLASSIC 110 Black 0,6/1 kV	43	✓	✓
ÖLFLEX® CLASSIC 110 CY Black 0,6/1 kV	44	✓	✓
ÖLFLEX® CONTROL TM	55	✓	✓
ÖLFLEX® CONTROL TM CY	56	✓	✓
ÖLFLEX® TRAY II	57	✓	✓
ÖLFLEX® TRAY II CY	58	✓	✓
NSSHÖU	92	✓	✓
ÖLFLEX® SERVO 720 CY		✓	
ÖLFLEX® SERVO 2YSLCY-JB	97	✓	✓
ÖLFLEX® SERVO 2YSLCYK-JB	97	✓	✓
ÖLFLEX® SERVO 719 CY	100	✓	✓
ÖLFLEX® SERVO 9YSLCY-JB	98	✓	✓
ÖLFLEX® SERVO 9YSLCY-JB BK	98	✓	✓
ÖLFLEX® SERVO 7DSL	102	✓	✓
ÖLFLEX® SERVO FD 781 CY	107	✓	✓
ÖLFLEX® SERVO FD 796 P	108	✓	✓
ÖLFLEX® SERVO FD 796 CP	109	✓	✓
SERVO LK SMS 6FX 8PLUS	113	✓	✓
SERVO cables in acc. to INDRAMAT® Standard INK	115	✓	✓
SERVO cables in acc. to LENZE® Standard	116	✓	✓
ÖLFLEX® CHAIN 809 SC	120	✓	✓
ÖLFLEX® CHAIN 809 SC CY	121	✓	✓
ÖLFLEX® FD 90	122	✓	✓
ÖLFLEX® FD 90 CY	123	✓	✓
ÖLFLEX® CHAIN 896 P	143	✓	✓

Certificate type			
Product	Page	Fire protection	EAC
<b>Halogen-free, flame retardant, flexible power cables, nominal voltage up to 1000 V</b>			
ÖLFLEX® CLASSIC 100 H	60	✓	✓
ÖLFLEX® CLASSIC 110 H	61	✓	✓
ÖLFLEX® CLASSIC 110 CH	62	✓	✓
ÖLFLEX® CLASSIC 130 H	63	✓	✓
ÖLFLEX® CLASSIC 135 CH	64	✓	✓
ÖLFLEX® CLASSIC 130 H BK 0,6/1 kV	66	✓	✓
ÖLFLEX® CLASSIC 135 CH BK 0,6/1 kV	67	✓	✓
ÖLFLEX® PETRO C HFFR	69	✓	✓
ÖLFLEX® PETRO FD 865 CP	142	✓	✓
H1Z2Z2-K	158	✓	✓
ÖLFLEX® TORSION FRNC	160	✓	✓
ÖLFLEX® TORSION D FRNC	160	✓	✓
<b>Flexible rubber cables, nominal voltage 450/750 V</b>			
H05RR-F	85		✓
H05RN-F	86	✓	✓
H07RN-F	87	✓	✓
H07ZZ-F	90	✓	✓
H01N2-D	91	✓	✓
H07RN8-F	95	✓	✓
<b>Flexible cables for conveyor technology</b>			
ÖLFLEX® CRANE NSHTÖU	169	✓	✓
ÖLFLEX® CRANE VS (N)SHTÖU	170	✓	✓
ÖLFLEX® CRANE PUR	171	✓	✓
ÖLFLEX® CRANE	172	✓	✓
ÖLFLEX® CRANE 2S	173	✓	✓
ÖLFLEX® LIFT	174	✓	✓
ÖLFLEX® LIFT T	175	✓	✓
ÖLFLEX® LIFT S		✓	✓
ÖLFLEX® CRANE F	176	✓	✓
ÖLFLEX® CRANE CF	177	✓	✓
ÖLFLEX® LIFT F	178	✓	✓
<b>Heat resistant cables and single cores</b>			
ÖLFLEX® HEAT 105 MC	180	✓	✓
ÖLFLEX® HEAT 125 SC	196	✓	✓
ÖLFLEX® HEAT 125 MC	181	✓	✓
ÖLFLEX® HEAT 125 C MC	182	✓	✓
ÖLFLEX® HEAT 180 SiHF	183	✓	✓
ÖLFLEX® HEAT 180 SiF	198	✓	✓
ÖLFLEX® HEAT 180 SiF/GL	201	✓	✓
ÖLFLEX® HEAT 180 SiD	200	✓	✓
ÖLFLEX® HEAT 180 SiZ	201	✓	✓
ÖLFLEX® HEAT 180 H05SS-F EWKF	184	✓	✓
ÖLFLEX® HEAT 180 MS	185	✓	✓
ÖLFLEX® HEAT 180 C MS	186	✓	✓
ÖLFLEX® HEAT 180 EWKF	187	✓	✓
ÖLFLEX® HEAT 180 EWKF C	188	✓	✓

Certificate type			
Product	Page	Fire protection	EAC
ÖLFLEX® HEAT 180 GLS	189	✓	✓
ÖLFLEX® HEAT 205 MC	190	✓	✓
ÖLFLEX® HEAT 205 SC	202	✓	✓
ÖLFLEX® HEAT 205 PTFE/FEP	190	✓	✓
ÖLFLEX® HEAT 260 MC	191	✓	✓
ÖLFLEX® HEAT 260 C MC	192	✓	✓
ÖLFLEX® HEAT 260 SC	203	✓	✓
ÖLFLEX® HEAT 260 GLS	193	✓	✓
ÖLFLEX® HEAT 350 MC	194	✓	✓
ÖLFLEX® HEAT 350 SC	204	✓	✓
ÖLFLEX® HEAT 650 SC	206	✓	✓
ÖLFLEX® HEAT 1565 MC	195	✓	✓
ÖLFLEX® HEAT 1565 SC	205	✓	✓
<b>Standard single cores, nominal voltage up to 1000 V</b>			
LiFY/LiFY 1 kV	149-150	✓	✓
H05V-K	210	✓	✓
X05V-K	212	✓	✓
H07V-K	213	✓	✓
X07V-K	216	✓	✓
H05Z-K 90° C	225	✓	✓
H07Z-K 90° C	226	✓	✓
Multi-Standard SC 1	217	✓	✓
Multi-Standard SC 2.1	218	✓	✓
Multi-Standard SC 2.2	221	✓	✓
<b>PVC power cables for buildings/infrastructure</b>			
NYM-J	230	✓	✓
NYY-J	232	✓	✓
NYY-O	232	✓	✓
NYCY	237	✓	✓
NYCWY	238	✓	✓
<b>Halogen-free, flame retardant power cables for buildings/infrastructure</b>			
(N)HXMH	231	✓	✓
N2XH	234	✓	✓
N2XCH	236	✓	✓
<b>Cable for railways vehicles</b>			
ÖLFLEX® TRAIN	156-157	✓	
UNITRONIC® TRAIN	367	✓	
ETHERLINE® TRAIN	450	✓	
<b>Data transmission cables: low/high frequency</b>			
ETHERLINE®			
UNITRONIC®			
UNITRONIC® BUS			
UNITRONIC® LAN and Coaxial cables			
don't subject to the "Low voltage directive" 2014/35/EU. They don't have mandatory certification and no EAC certificates.			
Fire certificates are available. Please contact us.			