

381167807	<b>DATA SHEET</b>	
Valid from: 11.07.2025	<b>EPIC® M23P 9-PIN INSERT MALE RECEPTACLE HV</b>	

### Description

- Inserts for circular connectors EPIC® M23P



### General features

Series	M23P
Version	Male
Pin configuration	3+PE+5
Rated voltage in V	1000 V (2 mm contacts, height 2000 m)
	optional 630 V (2 mm contacts, height 5000 m)
	250 V (1 mm contacts)
Rated impulse voltage	8 kV (2 mm contacts)
	4 kV (1 mm contacts)
Rated current in A	30 A (2 mm contacts, with terminal cross-section 4.0 mm <sup>2</sup> )
	7 A (1 mm contacts)
Contact resistance working contacts	< 4 mOhm
Contact resistance PE contact	< 100 mOhm
Contacts	To be ordered separately
Number of contacts	9 (3+PE+5)
Cable connection	Crimp connection: 0.35 - 4.0 mm <sup>2</sup> (2 mm contacts)
	Crimp connection: 0.05 - 1.0 mm <sup>2</sup> (1 mm contacts)
Mating cycles	500
Temperature range	-20°C to +130°C
	optional -50°C to +130°C (EPDM)
Pollution degree	3
Over Voltage Category	III

### Materials and surfaces

Contact carrier	PA
Insulating body	PA
PE contact	Copper Alloy

### Approvals

UL certification	Approval in pending
------------------	---------------------

Created: IVSE1/BU EPIC Released: THB01/BU EPIC	Document: DB381167807EN Version: 00	Page 1 from 2
---	--	---------------


381167807	<b>DATA SHEET</b>	
Valid from: 11.07.2025	<b>EPIC® M23P 9-PIN INSERT MALE RECEPTACLE HV</b>	

### Standard

Safety standard

IEC 61984; UL 1977; UL 2238

### Technical drawings



Industrial machinery and plant engineering



Robust



Good chemical resistance



Maximum vibration protection



Space requirement



Mechanical resistance



Waterproof



Corrosion resistant



Short assembly time



Wind energy

### Remark

The photographs are not true to scale and do not represent detailed images of the respective products.

Created: IVSE1/BU EPIC Released: THB01/BU EPIC	Document: DB381167807EN Version: 00	Page2 from 2
---	--	--------------