

381167808	<b>DATA SHEET</b>	
Valid from: 11.07.2025	<b>EPIC® M23P 9-PIN INSERT MALE</b>	

## Description

- Inserts for circular connectors EPIC® M23P



## General features

Series	M23P
Version	Male
Pin configuration	3+PE+5
Rated voltage in V	630 V (2 mm contacts, height 2000 m) 250 V (1 mm contacts)
Rated impulse voltage	6 kV (2 mm contacts) 4 kV (1 mm contacts)
Rated current in A	30 A (2 mm contacts, with terminal cross-section 4.0 mm <sup>2</sup> ) 7 A (1 mm contacts)
Contact resistance working contacts	< 4 mOhm
Contact resistance PE contact	< 100 mOhm
Contacts	To be ordered separately
Number of contacts	9 (3+PE+5)
Cable connection	Crimp connection: 0.35 - 4.0 mm <sup>2</sup> (2 mm contacts) Crimp connection: 0.05 - 1.0 mm <sup>2</sup> (1 mm contacts)
Mating cycles	500
Temperature range	-20°C to +130°C
	optional -50°C to +130°C (EPDM)
Pollution degree	3
Over Voltage Category	III

## Materials and surfaces

Contact carrier	PA
Insulating body	PA
PE contact	Copper Alloy

## Approvals

UL certification	Approval in pending
------------------	---------------------


Created: IVSE1/BU EPIC Released: THB01/BU EPIC	Document: DB381167808EN Version: 00	Page 1 from 2
---	--	---------------

381167808	<b>DATA SHEET</b>	
Valid from: 11.07.2025	<b>EPIC® M23P 9-PIN INSERT MALE</b>	

### Standard

Safety standard IEC 61984; UL 1977; UL 2238

### Technical drawings



Industrial machinery and plant engineering



Mechanical resistance



Robust



Waterproof



Good chemical resistance



Corrosion resistant



Maximum vibration protection



Short assembly time



Space requirement



Wind energy

### Remark

The photographs are not true to scale and do not represent detailed images of the respective products.

Created: IVSE1/BU EPIC Released: THB01/BU EPIC	Document: DB381167808EN Version: 00	Page2 from 2
---	--	--------------