


| | | |
|---------------------------|---------------------------------------|---|
| 44420241 | DATA SHEET |  |
| Valid from: 14.01.2019 | EPIC® POWERLOCK SCREW CONTACTS | |

Description

- Screw contacts for Powerlock circular connectors
- Tightening torque M12 nut: 27,5 Nm - 31,4 Nm



| Article- Number | Article | Version |
|--|------------------|--|
| Drain - contact with M12 threaded post, for type POWERLOCK A1 S | | |
| 44420241 | POWERLOCK SP M12 | Contact Drain, M12 Thread for cable lugs |
| Source - contact with M12 threaded post for type POWERLOCK A6 S | | |
| 44420242 | POWERLOCK QP M12 | Lamella contact source, M12 thread for cable lug |
| Source - screw contact for type POWERLOCK D6 S | | |
| 44420237 | POWERLOCK QS 120 | 120mm ² |
| Drain - screw contact, for type POWERLOCK F6 S | | |
| 44420232 | POWERLOCK SS 120 | 120mm ² |



Info

Max. screw 400 A

Do not plug with crimp-type (660 A)

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

| | | |
|---|---------------------------------------|-------------|
| Creator: STKU3/PDP Released: IVSE1/PDP | Document: DB44420241EN Version: 02 | Page 1 of 1 |
|---|---------------------------------------|-------------|