

70104200	DATA SHEET	
Valid from: 17.09.2018	EPIC® H-B 16 TSH-RO	

Description

- The housing standard.
- Wide choice for all applications.



General Characteristics

Series	H-B 16
Version	Hood PG21/ PG29 (Article 70104400)
Locking	Bolts with plastic rollers for single lever
Cable gland	Yes
Cable entry	Side
Protection	IP 65 (latched)
Temperature Range	-40°C to +100°C, short term up to +125°C

Materials and Surfaces

Housing	Aluminium alloy, powder-coated grey
Bolt with reels	Zinc plated steel / PA

Approvals

VDE-Approval, VDE-REG.-Nr.	B437
----------------------------	------


Standard

Safety Standard	IEC 61984
-----------------	-----------


Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB70104200EN Version: 01	Page 1 of 2
---	---------------------------------------	-------------

70104200	DATA SHEET	
Valid from: 17.09.2018	EPIC® H-B 16 TSH-RO	

Technical Drawings



Automation



Industrial machinery and plant engineering



Mechanical resistance



Robust



Waterproof

Info

Universal, robust metal housings size H-B 16

Application range

Plant engineering
Light & sound technology
Plastics industry

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB70104200EN Version: 01	Page 2 of 2
---	---------------------------------------	-------------