

DATA SHEET	6180 4261
FIPLOCK® NPT	Valid from: 15.03.2018

Our one-piece FIPLOCK® NPT connector for cable protection, with a NPT connection thread, made of specially modified, zero-halogen polyamide 6 is self-extinguishing and resistant against most chemical media commonly used. Due to its excellent UV-resistance, FIPLOCK® NPT is also perfectly suited for outdoor installations. With our brand new 360° interlocking system and an inside conduit seal, FIPLOCK® NPT complies with the highest possible protection class IP69 in combination with our FIPLOCK® corrugated conduits with fine and coarse profile. Being delivered in a pre-assembled state and easy to re-open by using a commercially available slotted screwdriver, FIPLOCK® NPT ensures significant time saving during installation and disassembly.



Fits with all corrugated conduits NW7-NW48 with fine and coarse profile.

Material:

PA6 MOD BS SGA

Technical Features:

Connecting thread

NPT 3/8" up to NPT 2"

Nominal wide

NW 10 up to NW 48

Protection class

IP66, IP67, IP68 and IP69 (IP69K) acc. to EN 60529

Depending on the used conduit

Temperature range

-50°C up to +120°C

Additional features:

Notched bar impact test

7-25 kJ/m² acc. to ISO 180

Fire classification

V0 acc. to UL94

Fire hazardous level

HL3 (R22 and R23) acc. to EN 45545-2

Free of halogen und cadmium

UV and weathering resistance

acc. to IS FIP

Color:

Black

Grey



Approbation:

Reference standards:

DIN EN 61386-1

DIN EN 61386-22

DIN EN 61386-23

Suitable conduits:

SILVYN® SPLIT

FIPLOCK® FPAF

FIPLOCK® HPAF


FIPLOCK® FPDF

FIPLOCK® HPDF

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

DATA SHEET	6180 4261
FIPLOCK® NPT	Valid from: 15.03.2018

Product drawing:



Dimension table:

Part No.	NW	Thread G	Thread- length L mm	Length H mm	Inner Diameter ID mm	Outer Diameter AD/OD mm	SW	Weight g
FIPLOCK® NPT Black								
6180 4261	10	NPT 3/8"	10,4	39,4	9,8	24,7	20	9,4
6180 4262	12	NPT 1/2"	13,5	44,5	13,0	28,5	22	12,7
6180 4263	17	NPT 1/2"	13,5	53,6	13,0	34,0	27	19,2
6180 4264	23	NPT 3/4"	14,0	54,1	18,4	41,7	26	28,3
6180 4265	29	NPT 1"	17,3	57,7	24,1	48,4	41	33,0
6180 4266	36	NPT 1-1/4"	18,0	71,7	32,2	59,7	52	67,7
6180 4267	48	NPT 1-1/2"	18,4	72,1	38,8	71,0	65	86,0
6180 4268	48	NPT 2"	19,2	72,9	50,8	71,0	65	87,2
FIPLOCK® NPT Grey								
6180 4269	10	NPT 3/8"	10,4	39,4	9,8	24,7	20	9,4
6180 4270	12	NPT 1/2"	13,5	44,5	13,0	28,5	22	12,7
6180 4271	17	NPT 1/2"	13,5	53,6	13,0	34,0	27	19,2
6180 4272	23	NPT 3/4"	14,0	54,1	18,4	41,7	26	28,3
6180 4273	29	NPT 1"	17,3	57,7	24,1	48,4	41	33,0
6180 4274	36	NPT 1-1/4"	18,0	71,7	32,2	59,7	52	67,7
6180 4275	48	NPT 1-1/2"	18,4	72,1	38,8	71,0	65	86,0
6180 4276	48	NPT 2"	19,2	72,9	50,8	71,0	65	87,2