

**HITRONIC® PCF DUPLEX FD PNC PVC-PVC**

DB28352702EN

valid from: 01.11.2014

### 1. Product Description

Cable designation: AT-V(ZN)Y(ZN)Y 2K200/230 *flex*  
J-V(ZN)Y(ZN)Y 2K200/230 *flex*

Splittable duplex polymer cladded glass optical fibre (PCF) indoor cable with non-metallic strain relief, PVC inner and outer sheath, flame retardant, for industrial environments with normal mechanical stress, suitable for drag chains

### 2. Application

PCF bus cable for PROFINET applications; Type C special applications (highly flexible, permanent movement)  
Applications with cable lengths up to 100m at 100Mbit/s data rate  
For direct connector assembly (single cable diameter 2.2 mm)

### 3. Cable Design



Cable construction	2x PCF fibre (polymer cladded fibre with ETFE buffer), non-metallic strain relief elements, PVC single cable sheath, stranded with two filler elements and central element, plastic fleece as wrapping, strain relief elements, PVC outer sheath
Cable inner sheath	PVC (special PVC-based compound)
Cable outer sheath	PVC (special PVC-based compound)
Colour of inner sheath	See fibre colour coding
Colour of outer sheath	Green (similar to RAL 6018)
Colour coding	Black, orange (with arrow printing)
Strain relief	Aramid yarns (in single and total cable construction)
Type of armouring	-

### 4. Optical and Physical Properties of Fibre

Attenuation	@ 650 nm	dB/km	≤ 10
	@ 850 nm	dB/km	≤ 8
Bandwidth	@ 650 nm	MHz x km	≥ 17
	@850 nm	MHz x km	≥ 20
Numerical Aperture			0.37
Core diameter		µm	200
Cladding diameter		µm	230

### 5. Thermal Properties

Operating temperature	-20°C up to +70°C
Installation temperature	-10°C up to +50°C
Storage temperature	-30°C up to +70°C

## HITRONIC® PCF DUPLEX FD PNC PVC-PVC

DB28352702EN

valid from: 01.11.2014

**6. Mechanical Properties**

Max. number of fibres		2
Fibre outer diameter (with buffer)		500 µm
Sub cable outer diameter		2.2 mm
Cable outer diameter		8.8 ± 0.3 mm
Cable weight		77 kg/km
Min. bending radius	fixed installation	130 mm
	occasional flexing	175 mm
Max. tensile strength	long term	800 N
	short term	1.000 N
Max. lateral pressure	long term	3.000 N/10 cm
	short term	5.000 N/10 cm
For use in drag chains*	bending cycles	> 3.500.000
	chains length	4.5 m
	speed	3 m/s
	acceleration	3 m/s <sup>2</sup>

\* Please note assembly guidelines T3  
(LAPP main catalogue)

**7. Chemical Properties**

PVC sub unit sheath	Non-aging, flame retardant, abrasion resistant
PVC outer sheath	Flame retardant, oil resistant, UV resistant, non-aging, abrasion resistant

**8. Features**

- Flame retardant according to IEC 60332-3-24 (optical fibre cables under fire conditions)
- Oil resistance - Oil resistant I according to UL 1581 section 480
- UV resistance - Sunlight resistant according to UL 1581 section 1200
- PROFINET Optical Fibre Cable Type C according to guideline  
"PROFINET Cabling and Interconnection Technology" Version 3.1 March 2014
- EC-Directive: This cable is conform to the 2011/65/EU (RoHS, Restriction of the use of hazardous substances)

**9. Product Range Overview**

Part number	Article designation	No. of Fibres	Outer Ø (mm)
28352702	HITRONIC® PCF DUPLEX FD PNC PVC-PVC	2	8.8