



ZODZ2.E352714 - POSITIONING DEVICES - COMPONENT

Positioning Devices - Component

See General Information for Positioning Devices - Component

U I LAPP GMBH
 SCHULZE-DELITZSCH STR 25
 70565 STUTTGART, GERMANY

E352714


Nonmetallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam.,		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Min. Install. Temp., °C(°F)	Resistant to UV Light	Material Flame Rating	Also Classified to [^] IEC 62275 and EN 62275
		mm(in.)			Min	Max				
		Min	Max		Min	Max				
61831001	11	1 (0.04)	21 (0.83)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831002	11	1 (0.04)	32 (1.26)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831003	11	1 (0.04)	40 (1.57)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831004	11	2 (0.08)	51 (2.01)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831005	11	2.5 (0.10)	32 (1.26)	180 (40)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831006	11	3 (0.12)	50 (1.97)	180 (40)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831007	11	3 (0.12)	79 (3.11)	180 (40)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831009	11	2.5 (0.10)	38 (1.50)	220 (49)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831010	11	2 (0.08)	45 (1.77)	220 (49)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-

61831020	11	5.5 (0.14)	85 (2.48)	540 (121)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831021	11	4 (0.16)	80 (3.15)	540 (121)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831022	11	8 (0.31)	100 (3.94)	540 (121)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831023	11	35 (1.38)	130 (5.12)	540 (121)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831024	11	35 (1.38)	158 (6.22)	540 (121)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831025	11	35 (1.38)	220 (8.66)	540 (121)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831026	11	34 (1.34)	233 (9.17)	700 (157)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831029	11	30 (1.18)	213 (8.39)	1080 (243)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831041	11	1 (0.04)	21 (0.83)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831042	11	1 (0.04)	32 (1.26)	80 (18)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-

61831049	11	2.5 (0.10)	38 (1.50)	220 (49)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831050	11	2 (0.08)	45 (1.77)	220 (49)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831051	11	3 (0.12)	50 (1.97)	220 (49)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831053	11	2 (0.08)	103 (4.06)	180 (40)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831054	11	3.5 (0.14)	78 (3.07)	220 (49)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831056	11	3.5 (0.14)	100 (3.94)	220 (49)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831060	11	3.5 (0.14)	63 (2.48)	540 (121)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831061	11	4 (0.16)	80 (3.15)	540 (121)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831062	11	8 (0.31)	100 (3.94)	540 (121)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831063	11	35 (1.38)	130 (5.12)	540 (121)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831064	11	35 (1.38)	158 (6.22)	540 (121)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831065	11	35 (1.38)	220 (8.66)	540 (121)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-
61831066	11	34 (1.34)	233 (9.17)	700 (157)	-40 (-40)	85 (185)	-10 (14)	-	V-2	-

Note - All models are for use within enclosures only.

Marking: Company name, catalog or model number, the Recognized Component Mark,  and, if published with the product, the product's maximum and minimum operating temperature, minimum installation temperature if below 0°C, minimum and maximum bundle diameter, loop tensile strength, type designation and/or declared mechanical strength on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2019-10-30

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019

UL LLC"