



<b>DATA SHEET</b>	0036260
<b>ÖLFLEX® SERVO FD 760 CP</b>	valid from : 31.03.2008

## Application

ÖLFLEX® SERVO FD 760 CP cables are high flexible feedback cables/sensor leads for resolvers, tachometer, encoders and rotor position sensors for the control of servo motors. They are among others for use in dry, damp or wet rooms. Considering the indicated temperature range an outdoor use is possible. ÖLFLEX® SERVO FD 760 CP cables are increased oil resistant and at room temperature generally resistant against acids and caustic solutions. The outer sheath of Polyurethane is resistant against high mechanical load, particularly to abrasion and scouring, cut resistant, microbe-proof and hydrolysis resistant. They are special for use in power chains, automatic manipulators and in permanently moved machine parts. Usage on motor drum guidance or under a strain of more than 15 N / mm<sup>2</sup> is not allowed. The screen is a protection against electrical interference. ÖLFLEX® SERVO FD 760 CP cables are not for heavy current and so they don't confirm to ECD 2006/95/EC (low voltage directive).

## Design

Design	in support to VDE 0812, VDE 0281 and VDE 0282		
Conductor	superfine wire strands of bare copper acc. to IEC 60228 resp. VDE 0295, class 6		
Core insulation	TPE (Thermoplastic Elastomer)		
Core identification	coloured		
Core identification code	0036 260	measurement: 9x0,5 CP	BU,WH,RD,PK,GN,YE,BN,BK,GY
	0036 760	measurement: 9x0,5 CP DESINA®	BU,WH,RD,PK,GN,YE,BN,BK,GY
Screen	braid of tinned copper , coverage = 85 % (nominal value)		
Outer sheath	Polyurethane compound TPU acc. to HD 22.10 S2 resp. VDE 0282-10, additional halogen free		

## Electrical properties at 20 °C

Nominal voltage	48 V AC
Operating peak voltage	450 V Uss
Test voltage	A-A: 2000 V AC A-S: 1000 V AC

## Mechanical and thermal properties

Temperature range	for flex. applications	-40 °C up to +80 °C max. conductor temperature
	fixed installation	-50 °C up to +80 °C max. conductor temperature
Min. bending radius	4 x cable diameter for fixed installation 12 x cable diameter for flex. applications	
Flammability	flame retardant in acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2	
Tests	acc. to IEC 60811-x-x resp. VDE 0473 part 811-x-x and VDE 0472	

elaborated by: TE-K: M. Herb / R. Krämer	Document: DB0036260EN	page 1 of 1
---	-----------------------	-------------