

**Technical data:**

nominal width	Connection thread	A mm	B mm	C mm	D <sub>min</sub> mm	E mm
3/8'	PG 11	29	37	14	11,0	27
3/8'	PG 13,5	29	37	14	11,0	27
1/2'	PG 16	35	40	14	14,5	29
3/4'	PG 21	42	44	14	20,0	30
1'	PG 29	47	56	21	25,0	36
1 1/4'	PG 36	58	70	21	33,5	38
1 1/2'	PG 42	69	75	21	38,5	38
2'	PG 48	83	87	24	49,5	45
3/8'	NPT 1/2'	29	35	14	11,0	27
1/2'	NPT 1/2'	35	40	14	14,5	29
3/4'	NPT 3/4'	42	45	14	20,0	30
1'	NPT 1'	48	56	19	25,0	36
1 1/4'	NPT 1 1/4'	58	70	21	33,5	38
1 1/2'	NPT 1 1/2'	69	75	21	38,5	38
2'	NPT 2'	83		22	49,5	45
2 1/2'	NPT 2 1/2'	95		25	61,0	67
3'	NPT 3'	114		25	75,0	73
4'	NPT 4'	140	321	29	99,0	89

52004790	<b>DATA SHEET</b>	
Valid from: 09.07.2018	<b>SILVYN® FDW</b>	

**Material:** body : cast iron, surface elektrogalvanised and chromated  
strain relief and earthing sleeve : steel  
sealing : nylon

**Features:** connection piece : nylon insulated inside  
in combination with SILVYN® EF, OR, HTDL, HCX, HFX conduit, this conduit connector forms  
a unit that is impervious to liquids and ensures continuous earthing in accordance with VDE 0113/12.73

**Approval:** No. : E 23018  
No. : 2884



For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Schmid/PDP Released: DAMU1/PDP	Document: DB52004790EN Version: 01	Page 2 of 2
-----------------------------------------------	---------------------------------------	-------------