

61713150	DATA SHEET	
Valid from: 03.07.2018	SILVYN® HIPROJACKET INDUSTRIAL	

The SILVYN® HIPROJACKET INDUSTRIAL is an extremely heat resistant conduit which is mostly used in combination with other conduits. It has a high insulation factor and is because of the iron oxide silicon cover resistant against small quantities of liquid steel.

The conduit is frequently used in glass factories, steel and aluminum foundries as well as in the ceramic industry.



Material:	Knitted fiberglass inner conduit Sheath of iron-oxide silicon
Colour:	Red
Temperature range:	+260°C long-term usage +1090°C for 20 minutes +1640°C for 15-30 seconds
Resistance:	Against small quantities of liquid steel, iron, glass etc.

Creator: PDP Released: DAMU1/PDP	Document: DB61713150EN Version: 02	Page 1 of 2
-------------------------------------	---------------------------------------	-------------

61713150	DATA SHEET	
Valid from: 03.07.2018	SILVYN® HIPROJACKET INDUSTRIAL	

Part No.	Designation	Diameter		PU (m)
		Inner (mm)	Outer (mm)	
61713150	SILVYN® HIPROJACKET INDUSTRIAL NW 6	6,0	11,0	30
61713151	SILVYN® HIPROJACKET INDUSTRIAL NW 10	10,0	15,0	30
61713152	SILVYN® HIPROJACKET INDUSTRIAL NW 13	13,0	18,0	30
61713153	SILVYN® HIPROJACKET INDUSTRIAL NW 16	16,0	22,0	30
61713154	SILVYN® HIPROJACKET INDUSTRIAL NW 19	19,0	25,0	30
61713155	SILVYN® HIPROJACKET INDUSTRIAL NW 22	22,0	28,0	30
61713156	SILVYN® HIPROJACKET INDUSTRIAL NW 25	25,0	31,0	30
61713157	SILVYN® HIPROJACKET INDUSTRIAL NW 29	29,0	35,0	30
61713158	SILVYN® HIPROJACKET INDUSTRIAL NW 32	32,0	38,0	30
61713159	SILVYN® HIPROJACKET INDUSTRIAL NW 35	35,0	41,0	30
61713160	SILVYN® HIPROJACKET INDUSTRIAL NW 38	38,0	44,0	30
61713161	SILVYN® HIPROJACKET INDUSTRIAL NW 41	41,0	47,0	30
61713162	SILVYN® HIPROJACKET INDUSTRIAL NW 44	44,0	50,0	30
61713163	SILVYN® HIPROJACKET INDUSTRIAL NW 51	51,0	57,0	30
61713164	SILVYN® HIPROJACKET INDUSTRIAL NW 57	57,0	63,0	30
61713165	SILVYN® HIPROJACKET INDUSTRIAL NW 64	64,0	70,0	30
61713166	SILVYN® HIPROJACKET INDUSTRIAL NW 70	70,0	76,0	30
61713167	SILVYN® HIPROJACKET INDUSTRIAL NW 76	76,0	82,0	30
61713168	SILVYN® HIPROJACKET INDUSTRIAL NW 83	83,0	89,0	30
61713169	SILVYN® HIPROJACKET INDUSTRIAL NW 89	89,0	95,0	30
61713170	SILVYN® HIPROJACKET INDUSTRIAL NW 95	95,0	100,0	30
61713171	SILVYN® HIPROJACKET INDUSTRIAL NW 102	102,0	108,0	30
61713172	SILVYN® HIPROJACKET INDUSTRIAL NW 114	114,0	120,0	30
61713173	SILVYN® HIPROJACKET INDUSTRIAL NW 127	127,0	133,0	30

Accessories:



SILVYN® AMG Cable Gland (metric/PG/45°/90°)

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: PDP Released: DAMU1/PDP	Document: DB61713150EN Version: 02	Page 2 of 2
-------------------------------------	---------------------------------------	-------------