


61797918	DATA SHEET	
Valid from: 03.07.2018	SILVYN® UI 511 EG	

The SILVYN® UI 511 EG is a straight conduit gland. It will be used in combination with the stainless steel protective conduit SILVYN® UI 511, particularly in heavy robotics but also in the steel and aluminium foundry industries, machine and apparatus building.



The conduit gland consists of:

Body	stainless steel
Earthing sleeve	tin plated steel
Clamp ring	Polyamide
Connector	stainless steel
O-Ring	NBR



Part No.	designation	 suitable to SILVYN® UI 511		SW	C	D	min. inner Ø
6179 7918	SILVYN® UI 511 EG M16/1	SILVYN® UI 511	⁵ / ₁₆ “	24	35	12	6,8
6179 7920	SILVYN® UI 511 EG M16/2		³ / ₈ “	24	35	12	9,8
6179 7926	SILVYN® UI 511 EG M20/3		¹ / ₂ “	27	37	13	13,9
6179 7928	SILVYN® UI 511 EG M25		³ / ₄ “	33	40	15	18,5
6179 7930	SILVYN® UI 511 EG M32		1.“	43	46	15	22,8
6179 7932	SILVYN® UI 511 EG M40		1 ¹ / ₄ “	52	52	16	30,8

Connecting thread: M16 bis M40

Temperature range: -45°C bis +105°C

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: PDP Released: DAMU1/PDP	Document: DB61797918EN Version: 01	Page 1 of 1
-------------------------------------	---------------------------------------	-------------