

68100150	DATA SHEET	
Valid from: 03.07.2018	SILVYN® FLEXILOK 90° PG	

SILVYN® FLEXILOK 90° PG is a one-part conduit gland with fast fit for a safety assembling. For the demounting you are using a screwdriver. The gland is suitable for SILVYN® FPAS and can be used in the machine- and plant constructions, control cabinet and building installation.



Material: PA66

Features: Fast assembling
Slim design
Suitable for fine and coarse conduits

Temperature range: -40°C up to +120°C

Colour: Grey (RAL 7031)
Black (UV-Resistant)

Norm reference: 
UL FILENUMBER E308201

Note: Free of halogen, silicon and cadmium

Protection class: IP 66

Dimension table:

Part no.	Part name	Thread	Conduit Ø mm	Total length mm	Thread length mm	Outer Ø mm	Inner Ø mm
Black							
6810 0150	SILVYN® FLEXILOK 90° PG	PG 9	16	43	10	21	10,5
6810 0155	SILVYN® FLEXILOK 90° PG	PG 11	16	43	10	21	10,5
6810 0160	SILVYN® FLEXILOK 90° PG	PG 13,5/1	16	44	11	21	14
6810 0170	SILVYN® FLEXILOK 90° PG	PG 13,5/2	21	47	11	26	14
6810 0165	SILVYN® FLEXILOK 90° PG	PG 16/1	21	47	11	26	14
6810 0175	SILVYN® FLEXILOK 90° PG	PG 16/2	21	47	11	26	14
6810 0180	SILVYN® FLEXILOK 90° PG	PG 21	28	57	12	34	19
6810 0185	SILVYN® FLEXILOK 90° PG	PG 29	34	65	12	41	24,5
Grey							
6810 0190	SILVYN® FLEXILOK 90° PG	PG 9	16	43	10	21	10,5
6810 0195	SILVYN® FLEXILOK 90° PG	PG 11	16	43	10	21	10,5
6810 0200	SILVYN® FLEXILOK 90° PG	PG 13,5/1	16	44	11	21	14
6810 0210	SILVYN® FLEXILOK 90° PG	PG 13,5/2	21	47	11	26	14
6810 0205	SILVYN® FLEXILOK 90° PG	PG 16/1	21	47	11	26	14
6810 0215	SILVYN® FLEXILOK 90° PG	PG 16/2	21	47	11	26	14
6810 0220	SILVYN® FLEXILOK 90° PG	PG 21	28	57	12	34	19
6810 0225	SILVYN® FLEXILOK 90° PG	PG 29	34	65	12	41	24,5

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB68100150EN Version: 01	Page 1 of 1
---	---------------------------------------	-------------