



DATA SHEET	0157515
DIN compensating cable KP 9 L-SY 2x1,5	valid from : 01.12.2008

Application

The compensating cable KP 9 L-SY 2 x 1,5 mm² is a PVC insulated cable with steel wire armouring which transmits the thermoelectric voltage of PtRh/Pt thermocouples. It is for flexible use and fixed installation in dry and damp rooms with medium mechanical load. They may only be installed outdoors with UV protection and in observation of the max. permitted temperature range. The steel wire armouring serves as mechanical protection.

Design

Conductor	1,5 mm ² (48 x 0,20 mm)
Conductor material	RCB/SCB alloying, accuracy class 2 according DIN 43722 Positive conductor: Cu (copper) Negative conductor: CuNi (cupronickel)
Core insulation	PVC compound
Core identification	Positive conductor: red Negative conductor: white
Core layering	Cores twisted together
Inner sheath	PVC compound, colour: white
Armouring	Galvanized steel wire braiding
Outer sheath	PVC compound, colour: white

Electrical properties

Limiting deviation class 2 ± 60 µV (± 5,0 °C) / measuring point temperature +1000 °C

Mechanical and thermal properties

Temperature range	occasional flexing: -5 °C up to +70 °C
Minimum bending radius	occasional flexing: 15 x cable diameter
Flammability	flame retardant in acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2

Originator: Frank Hörtnagl / PD-KL Approved: Werner Körner / TE	Document: DB0157515EN	page 1 of 1
--	----------------------------	-------------