

|                           |                                                 |                                                                                    |
|---------------------------|-------------------------------------------------|------------------------------------------------------------------------------------|
| 0163005                   | <b>DATA SHEET</b>                               |  |
| Valid from:<br>01.04.2019 | <b>IEC compensating cable KP 3 L 2x1,5 oval</b> |                                                                                    |

## Application

The compensating cable KP 3 L 2 x 1,5 mm<sup>2</sup> is a glass fibre insulated cable which transmits the thermoelectric voltage of PtRh/Pt thermocouples. It is for fixed installation in dry rooms and may only be installed outdoors with UV- and humidity protection and in observation of the max. permitted temperature range.

## Design

|                     |                                                                     |                    |
|---------------------|---------------------------------------------------------------------|--------------------|
| Conductor           | 1.5 mm <sup>2</sup> (48 x 0.20 mm)                                  |                    |
| Conductor material  | RCB/SCB alloying, accuracy class 2 according IEC 60584              |                    |
|                     | Positive conductor:                                                 | Cu (copper)        |
|                     | Negative conductor:                                                 | CuNi (cupronickel) |
| Core insulation     | Glass fibre covering                                                |                    |
| Core identification | Positive conductor:                                                 | orange marked      |
|                     | Negative conductor:                                                 | white marked       |
| Core layering       | Cores parallel next to each other                                   |                    |
| Outer sheath        | Glass fibre braiding with interweaved, orange identification thread |                    |

## Electrical properties

|                            |                                                         |
|----------------------------|---------------------------------------------------------|
| Limiting deviation class 2 | ±60 µV (±5.0 °C) / measuring point temperature +1000 °C |
|----------------------------|---------------------------------------------------------|

## Mechanical and thermal properties

|                        |                                                                 |                      |
|------------------------|-----------------------------------------------------------------|----------------------|
| Temperature range      | occasional flexing:                                             | -25 °C up to +200 °C |
| Minimum bending radius | occasional flexing:                                             | 12 x cable diameter  |
| Flammability           | flame retardant in acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2 |                      |

|                                         |                                      |             |
|-----------------------------------------|--------------------------------------|-------------|
| Creator: TOME/PCM<br>Released: ALTE/PDC | Document: DB0163005EN<br>Version: 02 | Page 1 of 1 |
|-----------------------------------------|--------------------------------------|-------------|

We reserve all rights according to DIN ISO 16016.

PD 0019/05\_04.18EN