## 0034250 DATA SHEET

valid from: 20.01.2025

## **UNITRONIC® CY PIDY (TP)**



## **Application**

UNITRONIC® CY PiDY (TP) is a screened data cable with individually sreened and sheathed twisted pairs for fixed installation.

The cable is used for data processing and control systems in process control.

Due to the double shielding, the cable is suitable for laying in electromagnetically loaded areas.

Design

Design based on standard VDE 0812

Conductor fine wire strands of bare copper acc. to IEC 60228 resp. EN IEC 60228, class 5

Insulation PVC compound TI52 acc. to EN 50290-2-21

Core identification code acc. to DIN 47100

Cable assembly screened and sheathed twisted pairs stranded in layers, optionally with fillers

wrapping with foil on the outer layer

Screen over each twisted core:

wrapping with plastic foil

Spinning with tinned copper wires, coverage 90 % (nominal value)

final screen:

Braiding with tinned copper wires, coverage 85 % (nominal value)

Outer sheath Sheath over each screened twisted pair:

special PVC-based compound colour: grey (similar RAL 7032)

Complete cable:

special PVC-based compound colour: grey (similar RAL 7032)

Electrical properties at 20 °C

Specific volume resistivity  $> 20 \text{ G }\Omega \text{ x cm}$ 

Mutual capacitance C/C: approx. 140 nF/km

C/S (pair): approx. 280 nF/km C/S (outer): approx. 150 nF/km

(at 800 Hz)

Inductance approx. 0.65 mH/km

Maximum operating voltage 250 V

(not intended to be used in conjunction with low impedance sources, such as power grids)

Test voltage 1200 V

Mechanical and thermal properties

Minimum bending radius occasional flexing: 15 x outer diameter

fixed installation: 6 x outer diameter

Temperature range occasional flexing: -5 °C up to +70 °C

fixed installation: -40 °C up to +80 °C

Flammability flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2

General requirements These cables are conform to EU-Directive 2011/65/EU

(RoHS, Restriction of the use of certain hazardous substances).

Environmental information These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).