



DATA SHEET	74400130
DMX 3035922 NC5MXX-B/NC5FXX-B	Valid from: 06.03.2008

1. Lapp type

DMX 3035922 NC5MXX-B/NC5FXX-B

2. Application

Assembled DMX cable (2 data pairs) for the transmission of light-control signals for professional stage lighting. The cable is assembled on both tails with a black 5-pole XLR connector from Neutrik. The characteristic impedance of the cable is 110 Ohm. The robust outer sheet is made of PUR.

3. Design

- Cable: No. 3035922 – UNITRONIC® DMX PUR PiMF CY BK
- (technical Detail, check Data sheet 3035922)
- Connector at tail 1: NEUTRIK® NC5MXX-BAG (XLR, 5-pole, black, male)
- Connector at tail 2: NEUTRIK® NC5FXX-BAG (XLR, 5-pole, black, female)

4. Layout

Tail 1:

Pin 1: shield (SLEEVE, Ground)

Pin 2: DATA 1-

Pin 3: DATA 1+

Pin 4: DATA 2-

Pin 5: DATA 2+

Tail 2:

Pin 1: shield (SLEEVE, Ground)

Pin 2: DATA 1-

Pin 3: DATA 1+

Pin 4: DATA 2-

Pin 5: DATA 2+

5. Available standard lengths

No. 74400130	DMX 3035922 1m NC5MXX-BAG/NC5FXX-BAG	1 m
No. 74400131	DMX 3035922 2,5m NC5MXX-BAG/NC5FXX-BAG	2,5 m
No. 74400132	DMX 3035922 5m NC5MXX-BAG/NC5FXX-BAG	5 m
No. 74400133	DMX 3035922 7,5m NC5MXX-BAG/NC5FXX-BAG	7,5 m
No. 74400134	DMX 3035922 10m NC5MXX-BAG/NC5FXX-BAG	10 m
No. 74400135	DMX 3035922 15m NC5MXX-BAG/NC5FXX-BAG	15 m
No. 74400136	DMX 3035922 20m NC5MXX-BAG/NC5FXX-BAG	20 m

Elaborated by: SBU: Martin Leuenberg	Document: DB74400130_EN	Page 1 of 1
---	-------------------------	-------------