



DATA SHEET	74400210
Speaker 3035378 NL4FX/NL4FX	Valid from: 06.03.2008

1. Lapp type

Speaker 3035378 NL4FX/NL4FX

2. Application

Assembled flexible speaker cable (4x2,5 mm²) for professional public address (PA) applications. Fine strands of plain copper wires, PVC- based cold flexible core insulation, cores twisted, outer sheath of special soft-PVC. The cable is assembled with a NEUTRIK[®] SPEAKON[®] connector on both tails.

3. Design

- Cable: No. 3035378 - UNITRONIC[®] SPEAKER LIYY BK
- (technical Details, check Data sheet 3035378)
- Connector at tail 1: NEUTRIK[®] NL4FX (SPEAKON[®])
- Connector at tail 2: NEUTRIK[®] NL4FX (SPEAKON[®])

4. Layout

Tail 1:

Pin 1+ = RED
Pin 1- = BLACK
Pin 2+ = BLUE
Pin 2- = WHITE

Tail 2:

Pin 1+ = RED
Pin 1- = BLACK
Pin 2+ = BLUE
Pin 2- = WHITE

5. Available standard lengths

No. 74400210	Speaker 3035378 1m NL4FX/NL4FX	1 m
No. 74400211	Speaker 3035378 2,5m NL4FX/NL4FX	2,5 m
No. 74400212	Speaker 3035378 5m NL4FX/NL4FX	5 m
No. 74400213	Speaker 3035378 7,5m NL4FX/NL4FX	7,5 m
No. 74400214	Speaker 3035378 10m NL4FX/NL4FX	10 m
No. 74400215	Speaker 3035378 15m NL4FX/NL4FX	15 m
No. 74400216	Speaker 3035378 20m NL4FX/NL4FX	20 m
No. 74400217	Speaker 3035378 25m NL4FX/NL4FX	25 m

Elaborated by: SBU: Martin Leuenberg	Document: DB74400210_EN	Page 1 of 1
---	-------------------------	-------------