



<b>DATA SHEET</b>	74400220
<b>Speaker 1233302 NL2FC/NL2FC</b>	Valid from: 06.03.2008

### 1. Lapp type

Speaker 1233302 NL2FC/NL2FC

### 2. Application

Assembled flexible speaker cable (2x4 mm<sup>2</sup>) for professional public address (PA) applications. Fine strands of plain copper wires, PVC- based cold flexible core insulation, cores twisted, outer sheath of special soft-PVC. The cable is assembled with a NEUTRIK<sup>®</sup> SPEAKON<sup>®</sup> connector on both tails.

### 3. Design

- Cable: No. 1233302 - UNITRONIC<sup>®</sup> SPEAKER LIYY BK
- (technical Details, check Data sheet 1233302)
- Connector at tail 1: NEUTRIK<sup>®</sup> NL2FC (SPEAKON<sup>®</sup>)
- Connector at tail 2: NEUTRIK<sup>®</sup> NL2FC (SPEAKON<sup>®</sup>)

### 4. Layout

Tail 1:

Pin 1+ = RED

Pin 1- = BLACK

Tail 2:

Pin 1+ = RED

Pin 1- = BLACK

### 5. Available standard lengths

No. 74400220	Speaker 1233302 1m NL2FC/NL2FC	1 m
No. 74400221	Speaker 1233302 2,5m NL2FC/NL2FC	2,5 m
No. 74400222	Speaker 1233302 5m NL2FC/NL2FC	5 m
No. 74400223	Speaker 1233302 7,5m NL2FC/NL2FC	7,5 m
No. 74400224	Speaker 1233302 10m NL2FC/NL2FC	10 m
No. 74400225	Speaker 1233302 15m NL2FC/NL2FC	15 m
No. 74400226	Speaker 1233302 20m NL2FC/NL2FC	20 m
No. 74400227	Speaker 1233302 25m NL2FC/NL2FC	25 m