



DATA SHEET	74400230
Speaker 3035379 NL4FX/NL4FX	Valid from: 06.03.2008

1. Lapp type

Speaker 3035379 NL4FX/NL4FX

2. Application

Assembled flexible speaker cable (4x4 mm²) for professional public address (PA) applications. Fine strands of plain copper wires, PVC- based cold flexible core insulation, cores twisted, outer sheath of special soft-PVC. The cable is assembled with a NEUTRIK[®] SPEAKON[®] connector on both tails.

3. Design

- Cable: No. 3035379 - UNITRONIC[®] SPEAKER LIYY BK
- (technical Details, check Data sheet 3035379)
- Connector at tail 1: NEUTRIK[®] NL4FX (SPEAKON[®])
- Connector at tail 2: NEUTRIK[®] NL4FX (SPEAKON[®])

4. Layout

Tail 1:

Pin 1+ = RED
Pin 1- = BLACK
Pin 2+ = BLUE
Pin 2- = WHITE

Tail 2:

Pin 1+ = RED
Pin 1- = BLACK
Pin 2+ = BLUE
Pin 2- = WHITE

5. Available standard lengths

No. 74400230	Speaker 3035379 1m NL4FX/NL4FX	1 m
No. 74400231	Speaker 3035379 2,5m NL4FX/NL4FX	2,5 m
No. 74400232	Speaker 3035379 5m NL4FX/NL4FX	5 m
No. 74400233	Speaker 3035379 7,5m NL4FX/NL4FX	7,5 m
No. 74400234	Speaker 3035379 10m NL4FX/NL4FX	10 m
No. 74400235	Speaker 3035379 15m NL4FX/NL4FX	15 m
No. 74400236	Speaker 3035379 20m NL4FX/NL4FX	20 m
No. 74400237	Speaker 3035379 25m NL4FX/NL4FX	25 m

Elaborated by: SBU: Martin Leuenberg	Document: DB74400230_EN	Page 1 of 1
---	-------------------------	-------------