

ÖLFLEX® TRUCK 170 TWIN

Battery cable and battery charging cable for tail lifts



Application

Battery cable used in between the power source and the end-user, e.g. from battery to the motor of tail lift. In addition to the easy handling and mounting of the cable there are a lot of other advantages for different actions.

Special Feature

Polarity identification is possible without stripping the sheath and an external marking (the plus pole is marked on the outer sheath). This prevents to connect the wrong cable. Additional advantages are: less abrasion of the sheath, flexible cores, cores do not brush after stripping, quick and easy to crimp.

Note

- Double sheathed version, extremely rough and therefore to lay without corrugated tubes!
- Very strong connection but nevertheless a wire separation by hand is possible.

ÖLFLEX® TRUCK 170 TWIN PLUS


LAPP-Article-No.: 7027 556
This cable combines all advantages of the ÖLFLEX® TRUCK 170 TWIN and has additionally 2 filler strands of 0,5 mm². These strands can be used as feedback to the charge station in case of constant charge control.


Further measurements or versions on request !


Cable Make-up


Fine strands of plain copper wires, PVC-based core insulation, outer sheath of a special PVC-based compound, black.


Technical Data


 Minimum bending radius for 15 x cable diameter

 Temperature range: -40 °C up to +85 °C (fixed) application range class A

 Conductor resistance: max. 0,554 at 20 °C

 Insulation resistance: 10 MOhm x km

 Nominal voltage 75 V DC

 Test voltage: 3000 V AC

Part number	Description	Colour code	Outer dimensions mm	Copper weight kg/km	on request
7027 055	PVC/PVC 2 x 6,0	red/black	15,2 x 7,1	120	
7027 056	PVC/PVC 2 x 10,0	red/black	18,8 x 8,9	200	
7027 057	PVC/PVC 2 x 16,0	red/black	21,0 x 10,0	320	
7027 058	PVC/PVC 2 x 25,0	red/black	25,6 x 12,3	500	
7027 059	PVC/PVC 2 x 35,0	red/black	28,0 x 13,5	700	*
7027 054	PVC/PVC 2 x 50,0	red/black	33,0 x 16,0	1000	*
7027 052	PVC/PVC 2 x 70,0	red/black	37,8 x 18,4	1400	*
7027 079	PUR/PVC 2 x 35,0	red/black	28,0 x 13,5	700	*
7027 049	Rubber insulated 2 x 35,0	black/black (printed)	21,8 x 10,4	700	*
7027 556	PVC/PVC 2 x 10,0 + 2 x 0,5	10,0 mm ² : red/black 0,5 mm ² : white/brown	21,8 x 10,4	210	

* further measurements on request !
No cutting costs are charged for standard lengths (50, 100, 500, 1000 m).
Please advise the lengths you require (e.g. 1 x 500 m drum or 5 x 100 m coil).
Coils < 30 kg, drums > 30 kg.
Copper base: 150,- Euro / 100 kg



Appendix 3:

Declaration of Non CCC Listing Products

To:
Shanghai Entry-Exit Inspection & Quarantine Bureau:

The details of imported goods we declare this time (Invoice Nr.: _____ • B/L
Nr.: _____) are as follows • •

Goods Description	H.S. Code	Type & Specification	Quantity/Weight

With concern of the CCC listing, we announce the above mentioned goods do not fall into the CCC listing. Attached please find the detailed technical documents:

We also hereby declare the imported goods listed above as well as the attached technical documents are true, and are willing to accept the monitoring and inspection of your organization at any time, and to take relative legal consequences if any.

Name of Consignee:
Contactor:
Telephone:
Date:
Company Seal: